

CENTRAL MAPPING AUTHORITY
GEODETTIC SURVEY OF N.S.W.

GEODETTIC STATION RECONNAISSANCE and MAINTENANCE REPORT

- Description:
1. Cleared by fences bearing..... STATION IS DIMENSIONED 560' from Trig. ~~LAST MARK~~
2. Mast & Vanes have been painted white & black respectively.
3. The station/pillar was unpainted/repainted/constructed on..... 1983, dimensions now being:
Description of mark: Steel Rod, should be explicit, e.g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe
Height of mark..... 0.50m above/below Soil Mark is AT..... m above/below G.L.
Height of Top Vanes to Top Mark/Pillar plate..... m. Diameter of Vanes (vertical)..... m.
Height of Cairn..... m. Diameter of Cairn..... m. Name Plate found/not found/altered.
No Beacon at this station (approximate if not unplied)
Length of Mast..... m. (approximate if not unplied)
4. A..... set in conc/rock has been placed/found, bearing..... M from Mast/Plug/Pillar
5. A..... set in conc/rock has been placed/found, bearing..... M from Mast/Plug/Pillar
6. A..... set in conc/rock has been placed/found, bearing..... M from Mast/Plug/Pillar
7. A..... set in conc/rock has been placed/found, bearing..... M from Mast/Plug/Pillar
8. Action required.....

STANDPOINT:	Mark	Direction	Horiz. Distance	Height Difference	Direction	Horiz. Distance	Height Difference
				above standpt			above standpt
				below standpt			below standpt
				above standpt			above standpt
				below standpt			below standpt
				above standpt			above standpt
				below standpt			below standpt
				above standpt			above standpt
				below standpt			below standpt
				above standpt			above standpt
				below standpt			below standpt
				above standpt			above standpt
				below standpt			below standpt

Prepared by: D. KAIN. Checked: D. KAIN.
 Noted on U.T.M. Card



