

Department of Lands Integration by of N.S.W. RECONNAISSANCE and MAINTENANCE REPORT 10177	STATION T.S. PLASHETT (P) TS 10177 Co: DORHAM Map Sheet: MUSNIE L1800K Inspected by: P. McPHERTH Authority: ISD NOLE Beacon Diagram Not to Scale 0.209 0.60 0.84 1.39 -33 -55 Record of Station Date 	This Trig. Station has been:- 1. Completely cleared to permit 360° vision to surrounding Trigs. ✓ 2. Cleared by Jones-bearing 3. Trig. Mast & Vanes have been painted white & black respectively. ✓ 4. The Trig. was unpiled/ not piled, dimensions now being: Description of mark: <u>concrete pillar</u> should be explicit, e.g. Steel plug, Brass plug, Bolt, Concrete Pillar Height of mark: <u>1.39</u> m above G.L. Height of Top Vanes to Top Top pillar plate: <u>1.44</u> m Diameter of Vanes (vertical): <u>0.60</u> m. Height of Cairn: <u>1.39</u> m. Diameter of Cairn: <u>33 x 55</u> m. Length of Mast: <u>1.53</u> m. (approximate if not unpiled) 5. <u>SSM 23805</u> set in conc/ rock has been placed <u>3.87</u> m. bearing <u>75</u> °M from Trig. Mast/pillar 6. A. <u>1.5</u> set in conc/ rock has been placed <u>3.60</u> m. bearing <u>341</u> °M from Trig. Mast/pillar 7. A. set in conc/soil has been placed <u>fd</u> m. bearing °M from Trig. Mast/pillar 8. A. set in conc/rock has been placed <u>fd</u> m. bearing °M from Trig. Mast/pillar 9. Connection <u>1.5</u> to <u>SSM 23805</u> ; <u>5.465</u> m. bearing <u>116</u> °M 10. Connection to m. bearing °M 11. Connection to m. bearing °M 12. Connection to m. bearing °M 13. Diff. Ht. <u>pillar plate</u> is <u>1.782</u> m. above <u>SSM 23805</u> 14. Diff. Ht. <u>pillar plate</u> is <u>1.206</u> m. above <u>1.5</u> 15. Diff. Ht. <u>1.5</u> is <u>0.573</u> m. above <u>SSM 23805</u> 16. Diff. Ht. is m. above/below Prepared by: <u>DP</u> Checked: <u>DP</u>
--	--	---

Integration by of N.S.W.

RECONNAISSANCE and MAINTENANCE REPORT 10177

Note: Cross out word or words which do not apply

This Trig. Station has been:-

1. Completely cleared to permit 360° vision to surrounding Trigs. ✓

2. Cleared by Jones-bearing

3. Trig. Mast & Vanes have been painted white & black respectively. ✓

4. The Trig. was unpiled/~~not~~ piled, dimensions now being:Description of mark: concrete pillar should be explicit, e.g. Steel plug, Brass plug, Bolt, Concrete PillarHeight of mark: 1.39 m above G.L.Height of Top Vanes to ~~Top~~ Top pillar plate: 1.44 m Diameter of Vanes (vertical): 0.60 m.Height of Cairn: 1.39 m. Diameter of Cairn: 33 x 55 m.Length of Mast: 1.53 m. (approximate if not unpiled)5. SSM 23805 set in conc/~~rock~~ has been placed 3.87 m. bearing 75 °M from Trig. Mast/pillar6. A. 1.5 set in conc/~~rock~~ has been placed 3.60 m. bearing 341 °M from Trig. Mast/pillar7. A. set in conc/soil has been placed fd m. bearing °M from Trig. Mast/pillar8. A. set in conc/rock has been placed fd m. bearing °M from Trig. Mast/pillar9. Connection 1.5 to SSM 23805; 5.465 m. bearing 116 °M

10. Connection to m. bearing °M

11. Connection to m. bearing °M

12. Connection to m. bearing °M

13. Diff. Ht. pillar plate is 1.782 m. above SSM 2380514. Diff. Ht. pillar plate is 1.206 m. above 1.515. Diff. Ht. 1.5 is 0.573 m. above SSM 23805

16. Diff. Ht. is m. above/below

Prepared by: DP Checked: DP

