LAND INFORM	LAND INFORMATION CENTRE		GEODETICS	SEODETIC SURVEY OF N.S.W.		ι			
	GEOC	DETIC STATION	GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT	E and MAINTEN	ANCE REPO	RT	STATION: BLAIR MORE	TS (5)	No.: (055.3
Description: 1. Cleared by lan	Description: Cleared by Janes bearing		Note: Cross out word or words which do not apply	or words which do not apfrom Trig, Mast	o not apply ig, Mast		- 2	ر	
2. Mast & Vanes	Mast & Vanes have been painted white & black respectively,	black respectively.					AUTHORITY:	SOUR CHELD BOOK	Delti 20 4 CS
3. The station/pil	The station/pillar was unpiled/not unpiled/constructed on	d/constructed on		19, dimensions now being:	now being:	· · · · · ·	036   046   086	-6	30,
Description of	Description of markshould be explicit, e.g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe	ld be explicit, e.g.,	S/Steel Pillar Plate,	Steel plug, Brass	plug, Bolt, G	l. Pipe	Station Diagram North	2	<b>}</b>
Height of mar	Height of markm. <sub>below</sub> rock/concrete;		Mark ism	m. above G.L.			Clearing, regi	for 15° h	Nozijan
Height of Top	Height of Top Vanes to Top Mark/Pillar platem.	platen		Diameter of Vanes (vertical)m.	tical)	Ė	numerous small of	large gum trees nall trees.	ses S
Height of Cairn	nm,	Diameter of Cairn	irnm.	Name Plate found/not found/placed.	nd/not found	/placed.	Mag. bearing	triagy,	
Length of Mas	Length of Mast (a	(approximate if not unpiled)	unpiled)				Harse 188 Visible	with clea	clearing of
4. A.	set in conc/rock has been placed/found, bearing	k has been placed/f	ound, bearing		from Mast/Plug/Pillar		Mitchell	138° not visible behind	puly
5. A	AA. set in conc/rock has been placed/found, bearing	k has been placed/f	ound, bearing		from Mast/Plug/Piliar		too many trees.	/ /// //	
6. A	A	k has been placed/f	ound, bearing	°M from Ması	t/Plug/Pillar		This end unknown	if tria visible	0/6 0/6
7. A	set in conc/rock has been placed/found, bearing <sup>©</sup> M from Mast/Plug/Pillar	k has been placed/f	ound, bearing	M from Mast	t/Plug/Pillar	<del></del>	because of trees at	1	er end.
8. Action require	8. Action required: Esta plash ownership, New mast and wines, olace we these.	vership, Ne	w mast and	vanes, polac	28 With	<u> </u>		end of large gum	a dam
STANDPOINT:	marks (none u	Jis16/le).	STANDPOINT:	\		_,	Martins Lockout 34	3	wattle
Mark	Direction Horiz.	Height Difference	Mark	Direction	Horiz. Hi	Height Difference	and gum trees this end.	is and.	<i>il-</i>
		above below				above standpt.	15 Dar Hill 13 Dac	Ked DV rise in	26 12
		above standpt.				above below standpt	Bon Novis 154° not visible behind	t visible	behind
		sbove standpt.					1045 of trees		<u> </u>
		above standpt.				above below standpt	Rumbee 227º C/e	lid of so	<i>∠.</i>
		above below standpt.				Boove standpt.		but piller	
		above standpt.				above standpt.	Seen.	<b>C</b> E	· 25
		above standpt.				above standpt.	0\$1 061 / 00Z / 01Z	170 160	150
Frepared by:		Checked:		No	Noted on U.T.M. Card	Card	Checked		
\$1.2733-1									

St 2733-2 D. West, Government Printer	STATION BLAIR MORE TS (P) 10553
Beacon Diagram	
	Owner's Name:
	Address:
	destruction on the property of the Contract of
	Phone: Phone
	ACCESS COULD be no Traingling
	KAN FORTING THE STATE OF THE ST
	0.00 Glen Innes Post Office traveleast along Manch Shoot toward bishim
	0.28 Turn right at roundapout onto Now Embad 1126
	head towards from ingine righted
	648 Cross Red Rook Cook
	070 101
	110 I WIN 18TT ONTO STONE NENGE FOOD STON SONDYN STUDY (150mts before)
	1048 Coses Wooden Loiden
	17.72 Cour way intersection straight ahead,
	13:11 Tass main road on L.H.S. Straight ahead at overn mailton
	1318 trate and Lind Public aste 479 TSP 'SANOW'SIGN SANOW
	14.68 Turn right of main track note definite with
	gate labt 100 motors to house)
This section to be completed by officer constructing pillar,	14.78 Iron gate sign 'TSR south Tish the Time Dag' " 11
Original station mark found/not found.	15.09 Pass old fence on 1.45
Description of mark:	15.5 Cross gully follow track.
	1604 Turn left off track note truck now many within it
Original beacon found/not found.	16.3 Turn light petage gate tollow, tenceling wound words side of hill.
Description of beacon;	16-68 7 win right at fence intersection.
	Date 16-78 Blancmore 7.5. Record of Station
Height lop of Vanes to lop Mark	
Height of markm. markm. rock/concm. Below G.L.	
WOING WATER	
Digitleter of Valley	
Original Beacon has/has not been destroyed by me.	