	CLEFT No.: 1487	CANBERRA	G.C.HANNA DATE: 27/3/79	C.M.A. FIELD BOOK:	350 360 10 20 30	North North Scale	0	E	ic.	60		70	80	90	100		160 <u>/</u>	720	_	136		<u>)</u>	46	150 180 170 160 150	Checked
	CENTRAL MAPPING AUTHORITY GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT STATION:	MAP SHEET SCALE 1:250 000	INSPECTED BY:	AUTHORITY: C	330 340	Station Diagram	· /	/ 0/	1É /	900 	/ 00	\$ \frac{1}{26}	280	570	560	0	SE	240		06Z	apri.)ZZ	4pt. / 210 / 200	The second secon
GEODETIC SURVEY OF N.S.W.		Description: Note: Cross out word or words which do not apply /	1. Cleared by lanes bearingfrom Trig. Mast	2. Mast & Vanes have been painted white & black respectively,	3. The station/pillar was unpiled/not unpiled/constructed on1919, dimensions now being:	be explicit, e.g., S/Steel Pillar Plate, Steel plug Brass plug Bolt, G.I. Pipe	Height of markm. below rock/concrete; Mark is	Height of Top Vanes to Top Mark/Pillar platem.	Height of Cairn	Length of Mast	4. Aset in conc/rock has been placed/found, bearing,	Aset in conc/rock has been placed/jound, beaping"M from Mast/Plug/Pillar	A	und, bearing" M from Mast/Piug/Pillar		STANDPOINT:	Mark Direction Distance Height Difference	above standpr	above above below standpt.	above standpt,	above standpt.	above standpt.	above standpt.	above standpt.	Noted on U.T.M. Card
CENTRAL MAPPING AUTHORITY						Description of markshould be explicit, e.g., S/								7. Aset in conc/rock has bs9h placed/jound, bearing	8. Action required:	\	Mark Direction Holys. Height Difference	above standpt	ahove standpt.	above standpt.	alove standpt.	above standpt.	above standpt.	above standpt.	Pronaved the OM 1014/70 Charked