

7-19-3

Department of Lands

Integration of N.S.W.

RECONNAISSANCE and MAINTENANCE REPORT

STATION **T.S. COWAN 1672**

This Trig. Station has been:

Note: Cross out word or words which do not apply

1. ~~Completed~~ cleared to permit 360° vision to surrounding trigs.
2. Cleared by lanes bearing $161^{\circ}M$ & $202^{\circ}M$ from Trig. Mast
3. Trig. Mast & Vanes have been painted white & black respectively. **No mast or vanes**
4. The Trig. was ~~applied~~/not unplied, dimensions now being:

Description of mark..... should be explicit, e.g. Steel plug, Brass plug, Bolt, Concrete Pillar

Height of mark..... m ^{above} rock/concrete m ^{below} G.L.

Height of Top Vanes to Top Mark/Top pillar plate..... m Diameter of Vanes (vertical)..... m.

Height of Cairn 1.8 m. Diameter of Cairn 3.25 m.

Length of Mast **No Mast** m. (approximate if not unplied)

5. A. **C.I.P.** set in conc. ~~rest~~ has been placed/fd 3.3 m. bearing 168 from Trig. ~~Mast/pillar~~

6. A..... set in conc./soil has been placed/fd..... m. bearing..... from Trig. Mast/pillar

7. A..... set in conc./soil has been placed/fd..... m. bearing..... from Trig. Mast/pillar

8. A..... set in conc./rock has been placed/fd..... m. bearing..... from Trig. Mast/pillar

9. Connection **T.S.** to **G.I.P.** 3.3 m. bearing 168 approx. dist. from center cairn

10. Connection..... to..... m. bearing..... M

11. Connection..... to..... m. bearing..... M

12. Connection..... to..... m. bearing..... M

13. Diff. Ht. is..... m. ^{above} below

14. Diff. Ht. is..... m. ^{above} below


15. Diff. Ht. is..... m. ^{above} below

16. Diff. Ht. is..... m. ^{above} below

Prepared by: **J. Cassidy** Checked: **[Signature]**

Co: **CUMBERLAND** Ph: **BROKEN BAY**
 Map Sheet: **MT. COLAH** No: **0967 III**
 Inspected by: **J. CASSIDY** Date: **24/6/82**
 Authority: **SCB** Field Book:

Beacon Diagram Not to Scale



Date	Record of Station

STATION: SCOWAN 1672

Owners Name... N.P. & W.S.
 Current Occupant.....
 Address... Kunzinggai
 Address.....
 Nat... Park

Access 24/6/1982
 * Note: Key to locked barrier on Perimeter Tr is obtained from ranger HQ. Bobbin Head Rd
 0.0 Intsn Booralie Rd and Mullawa Rd go NW along Mullawa Rd.
 0.7 Turn left and follow Bulara St.
 1.0 Turn right
 1.15 Turn left. Sign "Perimeter Tr" Go thru locked barrier and follow track.
 1.9 Intsn. Turn left and follow "Long track"
 2.75 Y intsn, take left track signposted "Cowan Tr"
 3.7 4WD needed to go further.
 Walk abt. 250M along track. Blazed gum on right. Cowan TS. off left of track abt. 20M.

