40 50 60 70 80 90 100 110 720 130 146

No.: 1993		1978	ok:) oc /	Not to Scalin	150	
		DATE:	FIELD BOOK:			160	
6.5	INE			- <u>-</u> -		0/1 0	
BLINE	KROMINE	OOK		0 360	± +	0 180	cked

\ ~				<u></u>	_	40	Z	<u>\$0</u>	Z	g6 /	. d€	वि०	90	100	360	7 7:										
No.: 1993		1978	FIELD BOOK:	/ be / /	Not to Scale												111		 T	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	19))			
2.5	E	DATE:	FIELD	þe / dı															Ē			170 180				
BLINE	NAKROWINE	R. COOK	4	350 360	North								+									190	. 2			
EUAMBELINE			ti cont	340)iagram																	61 / 002	1			
STATION:	MAP SHEET SCALE 1:250 000	INSPECTED BY:	AUTHORITY:	offe	Station Olagram		7	ois	700	, / ,	06ź /	 290	Tolz	\$60	/ 520	540	_	oez			<u></u>	9,5				
PORT				••		/		<u> </u>	7		<i>1 1</i> ,		<u> </u>	-11	Height Differance	Propue stander	above standpt	~~	athove standpt.		Schow standput	above standpt.	Card			
NANCE RE	do not apply	Trig. Mast	3	ıs now being	s plug, Bolt,		ertical)	und/not fou		st/Plug/Pilla	from Mast/Plug/Pillar	from Mast/Plug/Pillar	from Mast/Plug/Pillar	IE NORPE	Horiz. Distance						8.5		Noted on U.T. M. Card			
GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT	words which	from Trig. Mast		, dimensior	steel plug, Bra	shove G.L.	Diameter of Vanes (vertical)m.	Name Plate found/not found/placed.		°M from Ma				VO CLEARN	Direction								<			
	Note: Crass out word or words which do not apply	Mast & Vanes have been nationed active 8. Nach securities.		The second point and the second point of the s	g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe	Mark is m. above G.L.		Cairnm.	: unpiled)	A	5. Aset in conc/rock has been placed/found, bearing"M	6. Aset in conc/rock has been placed/found, bearing"M	7. Aset in conc/rock has been placed/found, bearing"M	8. Action required: N.Q. MAST. & MAGS. CAM. STALL STANDALG NO CLEARING NEEDED	Mark				P							
	Ne	Mast & Vanes have been nainted utrites & block secured:	a olace respectively	and bearing and the	Description of mark	/concrete;	/concrete;	(concrete;	/concrete;	/concrete;	Height of Top Vanes to Top Mark/Pillar platem.	Diameter of C	(approximate if not unpiled)	ok has been placed/	k has been placed/	k has been placed/	k has been placed/	S CONN STIL	Height Difference	stove below standpt	above standpt.	above standpt.	above standpt, below	above standpt.	above standpt.	shows standpt. below
GE		Latifum bate			shosho	below rock	Mark/Pillar	Ė	Ë	in conc/roc	in conc/rox	in conc/roc	in conc/roc	T 4 2/15	Horiz. Distance								41			
		s Dearing	,		lark. C.	Height of markm. below rock/concrets;	anes to Top	Height of Caim	Length of Mastm.	se:	set	tesset	set	NO MA	Direction								R. COOL			
	Description:	& Vanes h	tation/nilla		ption of m	t of mark	t of Top V	t of Caim.	h of Mast.					Action required:	Mark								Prepared by:			