	GEO	DETIC STATION	GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT	and MAINTENA	NCE REP	ORT	STATION: H	HERRING	6.5	No.:	No.: 2472
		No	Note: Crass out word or words which do not apply	words which do n	not apply		MAP SHEET SCALE 1:250 000		NARROMINE		
1. Cleared by lanes bearing			from Trig. Mast	from Trig.	. Mast		INSPECTED BY:	A. COOK.	. HC	DATE: 5677	77
have been painte	ed white &	2. Mast & Vanes have been painted white & black respectively.					AUTHORITY:	C.M.A.		FIELD BOOK:	
llar was unpiled/	not unpile	id/constructed on	3. The station/pillar was unpifed/not unpiled/constructed on	, dimensions no	ow being:	•	330 34	340 350	360 10	/ 20/	30,
mark, C. P. D	shou	ıld be explicit, e.g.,	Description of mark., R., R., R., R., B., Should be explicit, e.g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe	teel plug, Brass pl	ug, Bolt, (3.1, Pipe	Station Diagram	Ē	North	Not to Scale	cste
Height of markm. m. below rock/concrete;	above below rock/		Mark is m. below G.L.	above G.L.							
Vanes to Top M	lark/Pillar	Height of Top Vanes to Top Mark/Pillar plate		Diameter of Vanes (vertical).0.76m.	al) 0.76	Ë	7 ,				
Height of Cairn 2 .m.	Ę	Diameter of Ca	12.3 m.	Name Plate found/not found/placed.	I/not foun	d/placed.	'nέ				
t 3.86) .m.	Length of Mast38.66	unpiled)				008				
Aset in conc/rock h	n conc/roc	k has been placed/1	ias been placed/found, bearing"M from Mast/Plug/Pillar	°M from Mast/F	Plug/Pillar		: / 0				
set ir	n conc/roc	k has been placed/f	AA. from Mast/Plug/Pillar	°M from Mast/F	Plug/Pillar		6ź /				
set ir	n conc/roc	k has been placed/f	Aset in conc/rock has been placed/found, bearing"M from Mast/Plug/Pillar	°M from Mast/f	Plug/Pillar		580				
set ir	n conc/roc	k has been placed/f	7. Aset in conc/rock has been placed/found, bearing"M from Mast/Plug/Pillar	M from Mast/F	Plug/Pillar		270		+		
stall falls	Suited	Mast and Vo	8. Action required: Chinh. Ballan. Cines. Might, and Manan. Cit. Ann. Land. Exclamania. Charange STANDPOINT: STANDPOINT:	t Estern	nio ch	mereng	Seo /				
Direction	Horiz, Distence	Height Difference	Mark	Direction	Horiz, Distance	Height Difference	, żec				
		above standpt:				sbove standpt.	540				
		above standpt.				above below standpt.					
		above standet				above standpt.	230				
		above standpt.				above standpt.					
		above standpt.				above standpt,					
		above standpt.				above standpt.) Zz				
		above standpt.				ebove standpt.	/ 210 / 200	061 / 00	180	1/0 160	150
R ann											

nt 2733–2 D. West, Government Printer Beacon Diagram Nort to Scale	STATION HERRING G.S. TS 2472
	Phone:
	Drive to trig Up Ridge Line. Access found on the Fifield 1:50,000 sheet.
This section to be completed by officer constructing pillar. Original station mark found/not found,	
Description of mark:	
Original beacon found/not found.	
Description of bason:	Dalle Record of Station
Height fop of Vanes to Top Mark	SEDT 1978 STATION WISTED IN CONNECTION WITH field Completion.
Diameter of Varies	
Original Beacon has/has not bean destroyed by me.	