Cleaner by larse bearing.   Cleaner bearing.   Cleaner by larse bearing.   Cleaner by larse bearing.   Cleaner bearing.   Clea		CENTRAL MAPPING AUTHORITY	GEODETIC SURVEY OF N.S.W.	LEY OF M.S.W.					Ī
Pearly lives bearing.  Cleared by lares bearing.  Cleared by lares bearing.  Cleared by lares bearing.  Most & Verses have bean painted while & black respectively.  The station fuller was unplied/nonstructed on.  The station fuller was unplied/nonstructed on.  The station fuller was unplied/nonstructed on.  Demetry for mark.  A. Diameter of Common.  Demetry of Carlin.  Demetry of Mask is		GEOD	ETIC STATION RECONNAISSANCE an	nd MAINTENANCE P	EPORT	STATION:	ACOBS . 7		٥
Mat k   James bearing		Description:	Note: Cross out word or w	ords which do not app	Ap	MAP SHEET SCALE 1:250 000	8524 1.50 000		
Most & Vanes have been painted white & black respectively.  The station/pillar was unplied/constructed on		Cleared by lanes bearing		from Trig. Mast		INSPECTED BY:	J. SHERWIN	DATE:	S
The station/piller was unplied/nontriunded on horse.  The station/piller was unplied/nontriunded on horse.  Boernities and the explicit, e.g., S/Steel Pillar Plate, Steel plug, Briss plug, Bolt, G.I. Pipe  Begint of Cairn.  A. Biller on Cock/concrete;  Androon of was a fine concrete on Cairn.  Androon of was a fine was a fine concrete on Cairn.  Androon of was a fine was a fine concrete on Cairn.  Androon of was a fine was a f	7	Mast & Vanes have been painted white & !	olack respectively.			AUTHORITY:	CMA	FIELD BOOK:	Τ
Page	m		/constructed on19	., dimensions now bei	:Bu	-	350	/ 20 /	K
Height of mark to provide the late of Cairm		Description of markshould	d be explicit, e.g., S/Steel Pillar Plate, Stee	el plug, Brass plug, Bo	t, G.I. Pipe			Not to Scale	4
Height of Top Vanes to Top Mark/Pillar plate   Diameter of Calim		Height of markm. below rock/co		ove G.L.					ر /
Height of Cairn				of Vanes (vertical)	B				É
A		Height of Cairnm.		ame Plate found/not fo	und/placed.	ıε /			io
A.         Set in conc/rock has been placed/found, bearing			oproximate if not unpiled)			/ 00°E			/ g(
A	4,	Aset in conc/rock	has been placed/found, bearing	M from Mast/Plug/Pi	llar	/ 00			1
Au.         Set in conc/rock has been placed/found, bearing		Aset in conc/rock	has been placed/found, bearing	M from Mast/Plug/Pi		ž /			<del>}</del> e /
Auton required: CRNSTRUCK has been placed/found, bearing	ġ Q	Aset in conc/rock	has been placed/found, bearing	M from Mast/Plug/Pi		08Z			80
Action required:         CANSTRUCT         CLAR         CANSTRUCT	7.	Aset in conc/rock	has been placed/found, bearing"	M from Mast/Plug/Pi	llar	270	+		90
ANDPOLINT:         Horiz. below standpt.         Prection below standpt.         Direction below standpt.         Direction below standpt.         Prection st	∞	Action required: CONSTRUCT (	SILLAR - ONE DAYS C	KARING-DR	WE TO.	\$e0			100
Mark         Direction         Holyt Difference         Mark         Direction         Holyt Difference         Abricon standpring         Holyt Difference         Abricon standpring         Holyt Difference         Abricon standpring         Holyton standpring		STANDPOINT:	STANDPOINT:			09			1
Pagpared by:   Checked:   Check		Direction Distance				_ se			ilo /
Actions standpt.   Action standpt.   Actions standpt.   Action			above standpt.		above below standpt				<u>7</u> 20
Section standpr.   Section sta			above standpt.		above below standpt.				Z
Perconstruction   Perconstru			above standpt.		above helow standpt.				130
Secure Standbill   Secure Stan			above standpt,		above standpt. below				/
Section   Sect			above below standpt.		above standpt.	. 7			
Prepared by:  Aloned on U.T.M. Card  Checked:  Checked:			above standpt. below	-	above standpt.	ZZ			46
Prepared by: Checked: Noted on U.T.M. Card			above standpt.		above standpt.	/ 2/0 /	190	160	
			Checked:	Noted on U.	T.M. Card		Checked	20	

2733–2 D. West, Government Printer	STATION JACOBS T.S 2580
Not to Scale	Owner's Name: 2 (NOT KANOUN) Address: (NOT KNOUN)
	Phone: Phone: ACCESS  Access Report of 29.5/198,0,was found switeble/unsatiable.
	1.6 km South OF Wallace Chaigie Lowkout
	ON THE BARRY WAY TURN EAST OVER SMALL SHORE ON ONTO OLD FIRE TRAIL (VISIBLE UP OPPOSITE SIDE OF CLULY)
	DRIVE UP TO TOP OF RIDGE ON OTHER SIDE OF CAREK & TURN RIGHT.
This section to be completed by officer constructing pillar.  Original station mark found/nestarms.  Obscription of mark:	SMALL KNOB- &  DRIVE TO TOP OF KNOB (NO TRACK)
Original beacon found/not found,	
Height Top of Vanes to Top Mark	Date Record of Station
Д.	