

LAND INFORMATION CENTRE

GEODETTIC SURVEY OF N.S.W.

Batch 1702

GEODETTIC STATION: RECONNAISSANCE and MAINTENANCE REPORT

Description:

1. Cleared by lanes bearing Tree at 130°/190°/330° from Trig. Mast OK for GPS
2. Mast & Vanes have been painted white & black respectively.
3. The station/pillar was unpiled/not unpiled/constructed on 19 dimensions now being: Description of mark should be explicit, e.g., S/Steel Pillar/Plate/Steel plug, Brass plug, Bolt, G.I. Pipe
 Height of mark ROB ^{above} 19 m. _{below} G.L.
 Height of Top Vanes to Top Mark/Pillar plate ROB Diameter of Vanes (vertical) ROB m.
 Height of Cairn ROB m. Name Plate found/not found/placed. ROB
 Length of Mast ROB m. (approximate if not unpiled)
4. A. S.S.M. set in conc/rock has been placed/found, bearing 25° M from Mast/Plug/Pillar
5. A. set in conc/rock has been placed/found, bearing 25° M from Mast/Plug/Pillar
6. A. set in conc/rock has been placed/found, bearing 25° M from Mast/Plug/Pillar
7. A. set in conc/rock has been placed/found, bearing 25° M from Mast/Plug/Pillar
8. Action required: ROB

STANDPOINT:

Mark	Direction	Horiz. Distance	Height Difference	Mark	Direction	Horiz. Distance	Height Difference
			above standpt. below				above standpt. below
			above standpt. below				above standpt. below
			above standpt. below				above standpt. below
			above standpt. below				above standpt. below
			above standpt. below				above standpt. below
			above standpt. below				above standpt. below

Prepared by:

Checked:

Noted on U.T.M. Card

LTH -

STATION: **LOUTH** No.: **2898**

MAP SHEET **LOUTH**

SCALE 1:250 000

INSPECTED BY: **A. Svendsen** DATE: **22.3.95**

AUTHORITY: **LIC** FIELD BOOK: **/**

Checked

