

CENTRAL MAPPING AUTHORITY

Department of Lands

Trigonometrical Survey of N.S.W.

RECONNAISSANCE and MAINTENANCE REPORT

This Trig. Station has been:-

Note: Cross out word or words which do not apply

1. Completely cleared to permit 360° vision to surrounding Triggs.
2. Cleared by lanes bearing 250°M - 285°M 325°M from Trig. Mast
3. Trig. Mast & Vanes have been painted white & black respectively.
4. The Trig. was unpiled/not unpiled, dimensions now being: _____

Description of mark SMA Brass Plug in Conc. Fel. should be explicit, e.g. Steel plug, Brass plug, Bolt, G.I. Pipe

Height of mark m above below rock/concrete m above below G.I. Diameter of Vanes (vertical) m.

Height of Cairn m. Diameter of Cairn m.

Length of Mast m. (approximate if not unpiled)

5. A set in conc/rock has been placed m. bearing °M from Trig. Mast
6. A set in conc/soil has been placed m. bearing °M from Trig. Mast
7. A set in conc/soil has been placed 25° m. bearing °M from Trig. Mast
8. A set in conc/rock has been placed APP m. bearing °M from Trig. Mast

9. Connection to APP m. bearing °M

10. Connection to Not m. bearing °M

11. Connection to Not m. bearing °M

12. Connection to m. bearing °M

13. Diff. Ht. is m. above below

14. Diff. Ht. is m. above below

15. Diff. Ht. is m. above below

16. Diff. Ht. is m. above below

Prepared by: Page 10-3-77

Checked: Paul J. Paton

Noted on U.T.M. Card

STATION MARICA TS 2977

Co: Buccleuch Ph: Yarrangobilly

Map Sheet: Yarrangobilly No: 8526

Inspected by: A. D. Benga Date: 22nd February 1977

Authority Central Mapping Exp Yarrangobilly - S

Beacon Diagram Not to Scale

Timber Quadrupod in dis-repair.

No Vanes.

Note: Site suitable for pillar. Vehicular access to Trig.

Date

Record of Station

Checked

