CENTRAL WAPPING AUTHOR: 13							
	GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT	ECONNAISSANCE	IND MAINTENANCH	E REPORT	STATION: N.M.C	1.6 149	No.: 3450
e : E	Note	Note: Cross out word or words which do not apply	vords which do not	Ajdde	MAP SHEET SCALE 1:250 000	Canberra.	
Cleared by lanes bearing			from Trig. Mast	st	INSPECTED BY: P.K.Bamola	(Bamola.	DATE: 124 78
Mast & Vanes have been painted white &	hite & black respectively.			<b>J</b>		CMR	FIELD BOOK:
r was unpiled/not t	The station/pillar was unpiled/not unpiled/constructed on19		, dimensions now I	ceing:	330 340	350 360 1	10 / 20 / 39
ark	Description of markshould be explicit, e.g., S/Steel Pillar Platn, Steel plug, Brass plug, Bolt, G.I. Pipe	S/Steel Pillar Plate, St	oci plug, Brass plug,	Bolt, G.I. Pipe	Station Diagram	North	Not to Scale
Height of markm. below rock/concrete;		Mark ism. <sup>above</sup> G.L.	bove G.L.				
Height of Top Vanes to Top Mark/Pillar p	Pillar platem.		Diameter of Vanes (vertical)m.	.m.	0		
Height of Cairnm.	m. Diameter of Cairnm.		Name Plate found/not found/placed.	t found/placed.	16 /		
Length of Mastm.	m. (approximate if not unpiled)	inpiled)			005		
Aset in conc/rack		has been placed/found, bearing <sup>o</sup> M from Mast/Plug/Pillar	°M from Mast/Plug	//Pillar	/ 0		
Aset in conc/rock		has heen placed/found, bearing <sup>a</sup> M from Mast/Plug/Pillar	<sup>a</sup> M from Mast/Plug	y/Pillar	Ģź		
Aset in conc/rock		has been placed/found, bearing <sup>2</sup> M from Mast/Plug/Pillar	<sup>a</sup> M from Mast/Plug	//Pillar	1280		
Aset in conc/rock	nc/rock has been placed/for	. has been placed/found, bearing <sup>a</sup> M from Mast/Plug/Pillar	<sup>o</sup> M from Mast/Plug	/Pillar	0/2	+	
8. Action required: Mark Set In	of In Concrete	· Concrete, in Small ting of Stones Leans	ing of stan	es foand	500		
		STANDPOINT:			0		
Direction Dist	Hor'z. Distance Height Difference	Nark	Direction Ho	Horiz. Distance Height Difference	is \		
	above standpt. below			above standpt.	540		
	above standpt.			above standpt.	<u></u>		
	above standpt.			above standpt.	530		
	above standpt.			ahove stundpl. below			
	above standpt.			above standpt.			
	above standpt. below			above standpt.	ĴZZ		
1	ahova standpt. below			above standpt.	/ 210 / 200	1 081 1 061 /	170 160 150
K S	Z		Mated &	Mated as 11 T M. Davd		Chantand	

\_ \_ \_ \_ \_ \_

\_\_\_

	Owner's Name:	Current Occupant:
		Phone:
	Access Report of/19was found suitable.	
	Station drive-to	
	Refer Trainer Bridge 8527-1-N.	· N
This section to be completed by officer constructing piller.		
Original station mark found/not found.		
Description of mark:		
Original beacon found/not found.		10.0 E
Description of beacon:	Date Record of Station	
Height Top of Vanes to Top Mark		
Height of mark		
Diameter of Vanesm.m.m.m.		
Original Beacon has/has not been destroyed by me.		

G

. . .

\_\_\_\_