

CENTRAL MAPPING AUTHORITY

GEODETIC SURVEY OF N.S.W.

GEODETIC-STATION RECONNAISSANCE and MAINTENANCE REPORT

Access and Locality Sketch:

Particulars of station marking and beacon:

Apply

STATION MARK : 1/2" diam. copper tube inserted in 18" length of G.I. pipe in concrete block and marked with station number.

REFERENCE MARKS : Three 1/2" diam. copper tubes in concrete blocks. Blocks have been reinforced with 18" steel fence posts set directly beneath copper tubes. One 2" diam. steel witness post and a red painted blaze on a tree. Tree not found.

DESCRIPTION : MM C 65 is situated beside the road 9.1 miles from Cryon P.O. on the Burren Junction-Walgett road. It is in flat blacksoil country with scattered clumps of trees, and a 30 ft. tower was needed for all observations and measurements. Easy approach as shown. A trench 12" in diam. and approx. 12" deep has been dug around the station mark.

4. A.....set in conc/rock has been placed/found, bearing.....°M from Mast/Plug/Pillar
5. A.....set in conc/rock has been placed/found, bearing.....°M from Mast/Plug/Pillar
6. A.....set in conc/rock has been placed/found, bearing.....°M from Mast/Plug/Pillar
7. A.....set in conc/rock has been placed/found, bearing.....°M from Mast/Plug/Pillar

8. Action required:.....

Mark	Direction	STANDPOINT: N M C 65 Cu tube in conc.		Mark	Direction	Horiz. Distance	Height Difference
		Horiz. Distance	Height Difference				
N M C 64	0° 00'		above standpt below				above standpt below
R.M. Cu tube in conc.	156° 32'	9.760	above standpt below				above standpt below
R.M. "	212° 06'	10.406	above standpt below				above standpt below
R.M. "	288° 10'	10.290	above standpt below				above standpt below
			above standpt below				above standpt below
			above standpt below				above standpt below
			above standpt below				above standpt below

Prepared by: D.Fredriksen 25/10/19

Checked: Noted on U.T.M. Card

SK 2733-1



