

GEODETIC SURVEY OF N.S.W.

CENTRAL MAPPING AUTHORITY

GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT

STATION: NM/C/79 No: 3513

Access and Locality Sketch:

Particulars of station marking and beacon:

STATION MARK. 1/2" diameter copper tube inserted in a G.I. pipe driven to G.L. This is set in a concrete block marked with the station number.

BEACON. Nil.

REFERENCE MARKS.

Three 1/2" diameter copper tubes set in concrete blocks which have been re-inforced with steel pickets. One steel Witness Post and one red painted blaze on a tree.

ACCESS.

10.6 miles west of Mallett, along the Brewarrina road. It is sited on the north side of the road and close to the telephone line. Views are restricted to the clear line of the road, about 1/2 miles to the east and 4 miles to the west. A 10' tower was used for all observations and measurements. A 12" diameter trench was dug around the station mark in conc/rock has been placed.

- 6. A.....set in conc/rock has been placed/found, bearing.....°M from Mast/Plug/Pilla
- 7. A.....set in conc/rock has been placed/found, bearing.....°M from Mast/Plug/Pilla

8. Action required:.....

STANDPOINT:

STANDPOINT:

Mark	Direction	Horiz. Distance	Height Difference	Mark	Direction	Horiz. Distance
			above standpt			
			below			
			above standpt			
			below			
			above standpt			
			below			
			above standpt			
			below			
			above standpt			
			below			
			above standpt			
			below			
			above standpt			
			below			
			above standpt			
			below			

Prepared by: D. Fredriksen 25/10/79

Checked: Noted on U.T.M. Card

St 2735-1

MAP SHEET  
SCALE 1:250 000 ANGELDOOL

INSPECTED BY: D. Fredriksen DATE: 10/7/79

AUTHORITY: C. M. A. FIELD BOOK:

330	340	350	360	370	380	390
-----	-----	-----	-----	-----	-----	-----



