

GEODETIC SURVEY OF N.S.W.

CENTRAL MAPPING AUTHORITY

GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT

STATION: **NM/C/82** No: **3516**

Access and Locality Sketch:

Particulars of station marking and beacon:

STATION MARKS: 1" diameter copper tube in concrete block which is re-inforced with an 18" steel picket set directly below the copper tube. The station number is marked on the concrete block.

MAP SHEET SCALE 1:250 000 **WALGETT**
 INSPECTED BY: **D. Fredriksen** DATE: **10/7/79**
 AUTHORITY: **C. M. A.** FIELD BOOK:

BEACON: Nil.

REFERENCE MARKS:

Three 1/2" diameter copper tubes in concrete blocks. One steel Witness Post and one red painted blaze on a tree.

ACCESS:

NM/C/82 is sited on flat terrain close to the north side of the Walgett - Brevarrina road 19.8 miles west of Walgett. It was sited to see east for about 1 mile to the clearing along the telephone line and west for about 7/8 miles along the narrow cleared lane of the road. A 30' tower was needed for observations and measurements and a 12' diameter trench was dug around the station mark.

- 6. A.....set in conc/rock has been placed/found, bearing.....°M from Mast/Plug/Pillar
- 7. A.....set in conc/rock has been placed/found, bearing.....°M from Mast/Plug/Pillar
- 8. Action required:.....

STANDPOINT:

STANDPOINT:

Mark	Direction	Horiz. Distance	Height Difference	Mark	Direction	Horiz. Distance	Height
			above standpt				
			below				
			above standpt				
			below				
			above standpt				
			below				
			above standpt				
			below				
			above standpt				
			below				

Prepared by: **D. Fredriksen** 26/10/79 Checked:

Noted on U.T.M. Card

Checked



