

75-103

Department of Lands  
 RECONNAISSANCE and MAINTENANCE REPORT  
 Integrati. survey of N.S.W.

STATION TS 3755 PLEASANT (P)  
 Co: CUMBERLAND Ph: CASTLEREGHAT  
 Map Sheet: PENRITH No: U6460-III  
 Inspected by: J.L. FLETCHER Date: 20.1.78  
 Authority: DEPT. OF LANDS Field Book: 9643 & 13

This Trig. Station has been:-  
 Note: Cross out word or words which do not apply  
 1. Completely cleared to permit 360° vision to surrounding Trigs.  
 2. Cleared by lanes bearing ..... from Trig. Mast  
 3. Trig. Mast & Vanes have been painted white & black respectively.  
 4. The Trig. was unpiled/not unpiled, dimensions now being:

Description of mark: Steel plate on concrete pillar should be explicit, e.g. Steel plug, Brass plug, Bolt, Concrete Pillar  
 Height of mark ..... m above ~~rock~~ concrete ..... m above below G.L.  
 Height of Top Vanes to Top Mark/Top pillar plate ..... 1.477 m Diameter of Vanes (vertical) 0.60 m.  
 Height of Cairn ..... m Diameter of Cairn ..... m.  
 Length of Mast ..... m. (approximate if not unpiled)  
 5. A ~~concrete~~ steel set in ~~concrete~~ rock has been placed/fd 1.159 m. bearing 208° 14' 49" from Trig. Mast/pillar  
 6. A ~~concrete~~ steel set in ~~concrete~~ rock has been placed/fd 0.075 m. bearing 158° 29' 02" from Trig. Mast/pillar  
 7. A ..... set in conc/soil has been placed/fd ..... m. bearing ..... °M from Trig. Mast/pillar  
 8. A ..... set in conc/rock has been placed/fd ..... m. bearing ..... °M from Trig. Mast/pillar

9. Connection ..... to ..... m. bearing ..... °M  
 10. Connection ..... to ..... m. bearing ..... °M  
 11. Connection ..... to ..... m. bearing ..... °M  
 12. Connection ..... to ..... m. bearing ..... °M  
 13. Diff. Hr. ~~Correspondence~~ is 1.675 m. ~~above~~ below Pillar Plate.  
 14. Diff. Hr. ~~SSM 23734~~ is 1.770 m. ~~above~~ below Pillar Plate.  
 15. Diff. Hr. is ..... m. above below  
 16. Diff. Hr. is ..... m. above below

Prepared by: J.L. Fletcher Checked: J.L. Fletcher  
 Date ..... Record of Station



