			GEC	ODETIC STATION	GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT	and MAINTEN	ANCE REF	ORT	STATION: R	KANDALL		No.	No.: 3844
	Description:			No	Note: Cross aut word ar words which do not apply	words which do	not apply		MAP SHEET SCALE 1:250 000	NARROMINE	112		
<u>.</u>	Cleared by lanes bearing	bearing			from Trig. Mast	from Tri	g. Mast		INSPECTED BY:	G.C. HANNIA	۵	DATE: 26/9/78	81./6/
6	Mast & Vanes h	ave been painte	d white {	Mast & Vanes have been painted white & black respectively.					AUTHORITY:	C M. A.	Ľ.	FIELD BOOK:	U
m	The station/pills	ır was unpiled/i	not unpil	led/constructed on	The station/pillar was unpiled/not unpiled/constructed on19, dimensions now being:	, dimensions r	ow being:		330 340	9 350 360	0,	/ 50/	30
	Description of markshould	ıark	ous		be explicit, e.g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe	eel plug, Brass p	ofug, Bolt,	G.I. Pipe	Station Diagram	m North	<b>.</b> ‡	Not to Scale	cale
100.0	Height of markm. below rock/concrete;	al	bove e:ow rock	:/concrete;	Mark ism. Belowe G.L.	above G.L.			<u> </u>				
assed	Height of Top V	anes to Top Me	ark/Pillar	Height of Top Vanes to Top Mark/Pillar plate		Diameter of Vanes (vertical)m.	ical)	Ë	0,				
200000	Height of Cairn			Diameter of Ca	Diameter of Cairnm.	Name Plate found/not found/placed.	id/not fou	nd/placed.	ا اد				
0.000	Length of Mast .		Ë.	Length of Mastm. (approximate if not unpiled)	t unpiled)				300				
_	4. Aset in conc/rock	set in	i conc/roi	ck has been placed/	nas been placed/found, bearing" M from Mast/Plug/Pillar	.°M from Mast	/Plug/Pilla	_	: / o				
r,	Α	set in	r conc/ro	ck has been placed/	Aset in conc/rock has been placed/found, bearing M from Mast/Plug/Pillar	.°M from Mast	/Plug/Pilla	_	BŽ /				
. 9	Aset in conc/rock h	set in	conc/ro	ck has been placed/	nas been placed/found, bearing"M	.°M from Mast/Plug/Pillar	/Plug/Pilla	_	280				
7.	Aset in conc/rock !	set in	т сопс/га		as been placed/found, bearing" M from Mast/Plug/Pillar	.°M from Mast	/Plug/Pilla	L	0/2	1	+		
8.	Action required:				Action required:				560				
S	STANDPOINT:			, a	STANDPOINT:				0:				
	Mark	Direction	Horíz, Distance	Height Difference	Mark	Direction	Horiz. Distance	Height Difference	35 /				
				below standpt.				above below standpt.	240				
				above standpt.				above helow standpt.	7				
				above standpt.				above helow standpt.	<b>530</b>				
				above standpt.				above below standpt,					
			İ	above standpt.				above standpt.					
				above standpt, below				above standpt.	35(				
				above standpt.				above standpt.	210 / 200	190	180 170	160	150
	Drongrad hur C il	, ,					Manage 11 The Court	Page 1		č			

	S	STATION	75	3844
Beacon Diagram Not to Scale				
	Owner's Name:	Current Occup	Current Occupant:	
	Address:	Address:	Address:	*********
	***************************************	**************************************		***************************************
	Phone:	Phone:	Phone:	***************************************
		ACCESS		
	Access Report of 26, 3, 1918, was found suitable/unsuitable.	suitable.		
	700 000 00 00 00 00			
	Cairn O.5 m. Mast & Vanes fd.			
	360° vision with medium to heavy clearing	ยงการกฎ		
		4		
	Acness			
	On At Tullamore Hotel towards Narramine (North)	MINE (NOHN)		
	(T) Andrew Bridge (B. 1907)	(1) 4		
	3.4 R.H. torra park constraint			
	I.O. R 11 time of crosscords (Names of Charles	(5000)		
	TOTAL STREET STREET	(		
	2. O C. L. C. L. C.	ו סבוסבר ל סבים אינלואי		
This section to be completed by officer constructing pillar,	21:9 Start Table Co. modern Kond	i,		
Original station mark found/not found.				
Description of mark:				
Original beacon found/not found.	All measurements are approximate	iate.		
Description of beacon:	Date	Record of Station		
Height Top of Vanes to Top Mark				
Height of markm. below rock/concm below G.L.				
			***************************************	
Original Beacon has/has not been destroyed by me.				