

7498

Trigonometrical Survey of N.S.W.

RECONNAISSANCE and MAINTENANCE REPORT

Department of Lands

STATION ROSEWOOD TS 3952
 Co: Wynyard Ph: Carabost
 Map Sheet: Rosewood No: 8426
 Inspected by: N.D. Benge Date: 1st September 1976
 Authority: Central Mapping Authority Field Book:
 Beacon Diagram Not to Scale

This Trig. Station has been:-

1. Completely cleared to permit 360° vision to surrounding Trigs.
2. Cleared by James bearing from Trig-Mast
3. Trig-Mast & Vanes have been painted white & black respectively. Mast & Vanes destroyed.
4. The Trig. was unspiled/not unspiled, dimensions now being: ~~Original Station~~ G.L.

Description of mark..... should be explicit, e.g. Steel plug, Brass plug, Bolt, G.L. Pipe

Height of mark..... m above rock/concrete m below G.L.

Height of Top Vanes to Top Mark..... m. Diameter of Vanes (vertical)..... m.

Height of Cairn..... m. Diameter of Cairn..... m.

Length of Mast..... m. (approximate if not unspiled)

5. A..... set in conc/rock has been placed..... m. bearing.....°M from Trig. Mast
6. A..... set in conc/soil has been placed..... m. bearing.....°M from Trig. Mast
7. A..... set in conc/soil has been placed..... m. bearing.....°M from Trig. Mast
8. A..... set in conc/rock has been placed..... m. bearing.....°M from Trig. Mast
9. Connection..... to..... m. bearing.....°M Note: Site is suitable for pillar. However hill is within Carabost State Forest and is surrounded by pine trees. Vision will be completely blocked in a few years and the site will be unsuitable for observations for 10-15 years.
10. Connection..... to..... m. bearing.....°M
11. Connection..... to..... m. bearing.....°M
12. Connection..... to..... m. bearing.....°M
13. Diff. Ht. is..... m. above below
14. Diff. Ht. is..... m. above below
15. Diff. Ht. is..... m. above below
16. Diff. Ht. is..... m. above below

Prepared by: N. Benge Checked: Noted on U.T.M. Card

Record of Station

Date

