		SECT	FIICSIATION	GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT	and MAINTEN.	ANCE REF	ORT	STATION:	IKANGIE			2000
Description:			×	Note: Cross out word or words which do not apply	vords which do	not apply		MAP SHEET SCALE 1:250 000		NARROMNE		
1. Cleared by lanes bearing	жағілд		***************************************	from Trig. Mast	from Tr	ig. Mast		INSPECTED BY:		P. K Bamola.	DATE: Aug	3/8
2. Mast & Vanes have been painted white & black respectively. Gestroyrd	e been p <del>aintac</del> i	White &	slack respectivel	4. destroyed				AUTHORITY:	C.M.A	Ą	FIELD BOOK:	
3. The station/ <del>pilla</del> r	was u <del>mpi</del> led/no	t unpiled	/o <del>onstructed on</del>	The station/ <del>pilla</del> r was u <del>npi</del> led/not unpiled/o <del>onstructed on</del>	dimensions	Trow being:		330 34	340 350	360 10	/ joz /	30,
Description of markshould	rk	wshouk		be explicit, e.g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe	eel plug, Brass	plug, Bolt,	G.I. Pipe	Station Diagram	uu.	North	Not to Scale	- 44 - 88
Height of markm. m. below rock/concrete;	abor belo	ve ve rock/c	oncrete;	Mark is Below G.L.	stove G.L.			7				
Height of Top Vanes to Top Mark/Pillar plate	nes to Top Mark	k/Pillar p	late		Diameter of Vanes (vertical)m.	tical}		9				
Height of Cairn	2.11	Ë	Diameter of C	Diameter of Cairnm	Name Plate found/not found/placed.	nd/not foul	nd/placed.	ié /				0,
Length of Mastm. (ap		.m. (a	oproximate if not unpiled)	ot unpiled)				008				) éç
4. A	set in c	onc/rock	has been placed	Aset in conc/rock has been placed/found, bearing"M from Mast/Plug/Pillar	"M" from Mas	t/Plug/Pilla	_	- / 04				
5. Aset in conc/rock	set in c	onc/rock		has been placed/found, bearing"M from Mast/Plug/Pillar	°M from Mas	t/Plug/Pilla		5Z /				<u> </u>
6. A	set in c	onc/rock	has been placed	A has been placed/found, bearinget in conc/rock has been placed/found, bearinget	"M from Mas	from Mast/Plug/Pillar	_	zgo				80
7. Aset in conc/rock	set in c	onc/rock	has been placed	has been placed/found, bearing"M from Mast/Plug/Pillar	"Mi from Mas	t/Plug/Pilla		ozz		+		90
8. Action required: Mart & Vanco med to be a	Marta	Nane	ned ,	1	staced Station	Action		seo				100
STANDPOINT:	utable o	7	ullar ca.	STANDPOINT:				Os				)
Mark	Direction D	Horiz. P	Height Difference	Mark	Direction	Horiz. Distance	Height Difference	, şê				10 /
			Andve standpt.	e			above below standpt.	540				120
			above standpt.	-			above below standpt.	1				
		-	above standpt	t			above below standpt	530				130
			above standpt.	-			above standpt.	/				
			above standpt.	ē			above standpt.	- 6				/
			above standpt.	ı			above standpt.	350				46
	-		above standpt.	÷			above standpt.	/ 510 /	200 / 190	180	091 021	051
	,	0				Manage 11 T A. Com	J. Co.		Charles	trad		

St 2733-2 D. West, Government Printer	STATION / KANGIL	NG12 13 44-58
Beacon Diagram Not to Scale		
	Owner's Name:	Current Occupant:
	Address	Address:
	**************************************	ī
	Phone: description of the second of the seco	Phone:
	A: 1978 ACCESS	
	Access Report of/19was found suitable,	
		4.5% 000 co.
	Refer Narromina	/:30 000 00/
	Staller down	
	-	
		€3
This section to be completed by officer constructing pillar.		
Original station mark found/not found.		and the second
Description of mark:		
Original beacon found/not found.		
Description of Deacent: management of the second of the se	Date	Record of Station
Height Top of Vanes to Top Markm.		
Height of mark		
nt of Cairnm.		
Office of December 1 and the county becaused by me		
Original Descentias/institute and description by the		