

CENTRAL MAPPING AUTHORITY

GEODETIC SURVEY OF N.S.W.

GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT

Description:

1. Cleared by lanes bearing 270° and 230° . Note: Cross out word or words which do not apply
 from Trig. Mast

2. Mast & Vanees have been painted white & black respectively.

3. The station/pillar was unpiled/not unpiled/constructed on $5.2 \times 3.19.7.9$, dimensions now being:

Description of mark..... should be explicit, e.g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe

Height of mark..... m. above below rock/concrete; Mark is..... m. above below G.L.

Height of Top Vanees to Top Mark/Pillar plate..... m. Diameter of Vanees (vertical)..... 1.25 m.

Height of Cairn..... 1.6 m. Diameter of Cairn..... 2 m. Name Plate found/not found/p/aced.

Length of Mast..... 3.5 m. (approximate if not unpiled)

4. A..... set in conc/rock has been placed/found, bearing..... M from Mast/Plug/Pillar

5. A..... set in conc/rock has been placed/found, bearing..... M from Mast/Plug/Pillar

6. A..... set in conc/rock has been placed/found, bearing..... M from Mast/Plug/Pillar

7. A..... set in conc/rock has been placed/found, bearing..... M from Mast/Plug/Pillar

8. Action required.....

STANDPOINT:

Mark	Direction	Horiz. Distance	Height Difference	Mark	Direction	Horiz. Distance	Height Difference
			above standpt.				above standpt.
			below standpt.				below standpt.
			above standpt.				above standpt.
			below standpt.				below standpt.
			above standpt.				above standpt.
			below standpt.				below standpt.
			above standpt.				above standpt.
			below standpt.				below standpt.
			above standpt.				above standpt.
			below standpt.				below standpt.

Prepared by: *W.M. Miller* 26.2.79 Checked: *Checked*

SI 2733-1

Noted on U.T.M. Card

STATION: **TUMANANG** No.: **4465**
 MAP SHEET SCALE 1:250 000 **CANBERRA**
 INSPECTED BY: **W MILLER** DATE: **5.2.79**
 AUTHORITY: **C.M.A** FIELD BOOK:

Station Diagram

