| Description: 1. Cleared by lanes bearing | GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT | - BONASSIANOCES | nd MAINTENAN | LCE QEDODT | - | | SM 712 | O |
|---|--|--|---------------------|------------------------------------|-------------------------|------------------------------|-------------|------------------|
| Description: Cleared by lanes bearing | | יביטועיים עווערטיים ו | | יחטישה שטי | ST | O SINDIN: | M.H. 160-1 | 10. TBZ |
| Cleared by lanes bearing | | Note: Cross out word or words which do not apply | vords which do n | ot apply | SCA | MAP SHEET SCALE 1:250 000 | TANTAN GARA | 1:100,000 |
| Mast & Vanes have been painted white | | from Trig. Mast | from Trig. | Mast | SNI | INSPECTED BY: | R. COOK | DATE: 10-3-79 |
| The station (millian som solling) as the sal | & black respectively. | | | | A | AUTHORITY: | C.M. D. | FIELD BOOK: |
| 3. THE STATION FINAL WAS UNDIRECTOR TO THE STATION OF THE STATION | iled/constructed on | 19 | dimensions no | w being: | | 330 340 | 380 |) pc / pc / dt |
| Description of mark. "!! Steel Pillar Plate, Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe | ould be explicit, e.g., | S/Steel Pillar Plate, St | eel plug, Brass plu | ig, Bolt, G.I. Pipe | 928 | Station Diagram | North | Not to Scale |
| Height of markm. m. below rock/concrete; | k/concrete; | Mark is m. above G.L. | bove G.L. | | - / | | | |
| Height of Top Vanes to Top Mark/Pillar plate | ar platen | | of Vanes (vertica | Diameter of Vanes (vertical)m. | 9 | | | |
| Height of Cairn, | | Diameter of Cairnm. | ame Plate found | Name Plate found/not found/placed. | ię / | | | |
| Length of Mastm. (approximate if not unpiled) | (approximate if not | unpiled) | | | 000 | • | | è |
| AA. from Mast/Plug/Pillar Aset in conc/rock has been placed/found, bearing | ock has been placed/f- | ound, bearing | °M from Mast/P | lug/Pillar | /0 | | | |
| 5. A | ock has been placed/fe | ound, bearing | °M from Mast/P | lug/Pillar | 6 2 / | | | , γ Λ |
| 6. Aset in conc/rock has been placed/found, bearing"M from Mast/Plug/Pillar | ock has been placed/f | ound, bearing | M from Mast/P | lug/Pillar | 280 | | | <u>ģo</u> |
| 7. Aset in conc/rock has been placed/found, bearing"M from Mast/Plug/Pillar | ock has been placed/fi | ound, bearing | °M from Mast/P | lug/Pillar | 5.10 | | + | , ao |
| 8. Action required: "Remaine R. H. Bosader peach. an groom ch Schashach Cleaning Action required: Remainer Remainer Trains walk | solvitore an gros | und Schaffential | clearing nee | ded 15 min inc | Zeo Zeo | | | ∫ 1ģ0 |
| STANDPOINT: | | STANDPOINT: | | 2 | 09 | | | |
| Mark Direction Distance | Height Difference | Mark | Direction | Horiz. Height Difference | 1 | | | |
| | above standpt. | | | above | above standpt. | | | |
| | above standpt, | | | abova below | above below standpt. | | | |
| | anove standpt. | SMCCC STATEMENT OF STATEMENT | | above below | sbove standpt. | | | / |
| | above standpt. | | | above | above standpt, | | | |
| | above standpt. | | | above below | above below standpt. | | | |
| | above standpt. | | | woled . | below standpt. | | | |
| | above standpt. | | | above below | above standpt. | 2,10 / 200 | 1 081 061 | 170 160 150 |
| Prepared by: Rohan Gook | Checked: | | Note | Noted on U. T.M. Card | | | Checked | |

| Bt 2733-2 D. West, Government Printer | STATION | S.M.A. 764 TS 482 |
|--|---|---|
| Beacon Diagram Not to Scale | Ouron's Maner | Current Constants |
| | Address Strates within the | Address: |
| | KOSCUSKO NATIONAL PARK | |
| | Phone: | Phone: |
| | ACCESS | |
| | Access Report of 10.1.3./1921.was found suitable, unsuitable. | |
| | South the second | |
| | | |
| | | NORTH |
| | 000 | |
| | 7 | |
| | 9051 | |
| | 181 | - |
| | | |
| | Carlo Carlo | - |
| | | 5 Scale 1:25,000 |
| | MURKUMBIDGEE | |
| This section to be completed by officer constructing pillar. | Tow canney do | |
| Original station mark found/not found. | \$ SIN. W. 764 | |
| Description of mark: | 1161 | |
| Original beacon found/not found. | and the second | |
| Description of beacon: | 7 755 | Director of Charles |
| Height Top of Vanes to Top Mark | | or station |
| e.G.L. | 18-3-19 Recommensorans of Tois during held lamplation of Tantangara 1:25,000 Acres taken of the Transagara 1:25,000 | e during States Completion of Tentangara 1:25,000 |
| Diameter of Vanesm. Height of Cairnm. | | |
| Original Beacon has/has not been destroyed by me. | | |
| | | |