									(I)	٠	Ļ
		GEO	DETIC STATION	GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT	nd MAINTENAN	ICE REPOR	₹T.	STATION:	DHULHURA	A	No.: 5045
Description:			No	Nate: Crass out word or words which do not apply	ords which do n	ot apply		MAP SHEET SCALE 1:250 000	WALCA	WAGCA	
ared by Janes	Cleared by Janes bearing			from Trig. Mast	from Trig.	Mast		INSPECTED BY:	PALAKER	DATE:	30.10.78
t & Vanes ha	we been painted w	white &	Mast & Vanes have been painted white & black respectively,					AUTHORITY:	CM.A.	FIELD	FIELD BOOK: 1592
station/pilla	ir was unpiled/not	t unpile	d/constructed on	The station/pillar was unpiled/not unpiled/constructed on19 dimensions now being:	, dimensions no	w being:		330 340	350 360	10 / 20	, όε / ş
cription of m	ark	nous	ıld be explicit, e.g.,	Description of markshould be explicit, e.g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe	el plug, Brass plu	ıg, Bolt, G.I	. Pipe	Station Diagram	North		Not to Scale
ght of mark	Height of markm. Below rock/concrete;	" rock/		Mark is m. below G.L.	How G.L.			<u> </u>			
ght of Top V	anes to Top Mark	k/Pillar ı	Height of Top Vanes to Top Mark/Pillar plate		Diameter of Vanes (vertical)m.	(II	Ę	0,			
ght of Cairn	Height of Cairn	Ę	Diameter of Ca	Diameter of Cairnm.	Name Plate found/not found/placed.	'not found/	placed.	ιέ /			
ngth of Mast		Ë.	Length of Mastm. (approximate if not unpiled)	unpiled)				7 0,00			
	4. Aset in conc/rock h	onc/roc	k has been placed//	ias been placed/found, bearing" M from Mast/Plug/Pillar	M from Mast/P	lug/Pillar		: /0			
	set in co	onc/roc	k has been placed/	AB. from Mast/Plug/Pillar	M from Mast/P	lug/Pillar	(.l.	ięż /	CRIGINAL	STATION	
	Aset in conc/rock h	onc/roc	k has been placed/1	ias been placed/found, bearing"M from Mast/Plug/Pillar	M from Mast/P	lug/Pillar		- 580 - 580		25.1.1877.	
	Aset in conc/rock h	опс/гос	k has been placed/1	as been placed/found, bearing"M from Mast/Plug/Pillar	M from Mast/P	lug/Pillar	J I	270	+	F 57.5	
ion required:				8. Action required:		000000000000000000000000000000000000000		092			
STANDPOINT:				STANDPOINT:				1/2	EVIDENCE OF	OF MARK. P	PRETIONS
Mark	Direction Dis	Horiz, Distance	Height Difference	Mark	Direction	Horiz, Distance	Height Difference	AREA IS	TO BE	Sown	Becombaky, To
			above standpt				shove standpt.	NHE	5176	ĸ	SUITABLE
			abave standpt.				above below standpt.	AS LEC	LEODENC STA	STATION.	
		İ	above standpt.				above standpt.	530			
			above standar.				above standpt,				o secolite
			above standpt.				shove standpt.				
			above standpt.				above standpt.)दर्			
			above standpt.				above standpt.	00/2 / 01/2	190 180	1,00	180 150
Pronarod Inc.	11.11	1	15.11.78 Charlant	7.	Motor	Motor on UT M Card	arn		Chookad		

Beacon Diagram Not to Scale	Owner's Name. LAN Essav. Bussause." Address: Via CCOLMON Response. Phone: WACCA ACCESS Access Report of 39, 19, 1938, was found suitable/unsuitable.	Current Occupant:
	Access Report of <u>59</u> , IB,/1974, was found sultable/unsultable.	
This section to be completed by afficer constructing pillar.		
Original station mark found/not found.		
Description of mark:		
Original beacon found/not found.		
Description of beacon:	Date	Berro ii of Station
		in order
Height of markm. below rock/concm. below G.L.		UM CONTRACTOR DE LA CONTRACTOR CO
Diameter of Vanes		
Original Beacon has/has not been destroyed by me.		