CENTRAL MAPPING AUTHORITY	ING AUTHORITY	~		GEODETIC SURVEY OF N.S.W.	VEY OF M.S.W.		L			-
		GEO	DETIC STATION	GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT	and MAINTENA	NCE REPO	RT	STATION: SMA	4 0892	No.: 505
Description:			Non	Note: Cross out word or words which do not apply	vords which do	not apply		MAP SHEET SCALE 1:250 000	BEGA	
1. Cleared by lane	Cleared by lanes bearing			from Trig. Mast	from Tríg	. Mast	<u> </u>	INSPECTED BY:	G. KEEP	DATE: 27 5 80
2. Mast & Vanes h	ave been painted	d white 8	Mast & Vanes have been painted white & black respectively.					AUTHORITY:		FIELD BOOK:
3. The station/pill	ar was unpiled/n	ot unpile	d/constructed on	The station/pillar was unpiled/not unpiled/constructed on	, dimensions n	ow being:		330 340	350 360	02 / 50/ 01
Description of r	Description of markshould	shou	ıld be explicit, e.g.,	be explicit, e.g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe	eel plug, Brass pi	lug, Bolt, G		Station Diagram	North	Not to Scale
Height of mark	Height of markm. below rock/concrete;	sove rock/		Mark is m. above G.L.	bove G.L.			7		
Height of Top	anes to Top Ma	ark/Pillar	Height of Top Vanes to Top Mark/Pillar platem.		Diameter of Vanes (vertical)m.	sal)		∕ _{0,}		
Height of Cairn	Height of Cairn	B.	Diameter of Ca	Diameter of Cairnm.	Name Plate found/not found/placed.	//not found		<u> </u>		
Length of Mast			Length of Mastm. (approximate if not unpiled)	unpiled)			<u>-</u> /			
4. A.	ni tes	conc/roc	k has been placed/f	AA. from Mast/Plug/Pillar A	°M from Mast/	Plug/Pillar	<i></i>	/0		
5. A	set in	conc/roc	k has been placed/f	A	M from Mast/	Plug/Pillar	<i>!</i>	sź /		
6. A.	ni 198	conc/roc	k has been placed/f	A Aset in conc/rock has been placed/found, bearings	°M from Mast/Plug/Pillar	Plug/Pillar	,	08Z		
7. A.	m set in	conc/roc	k has been placed/f	7. Aset in conc/rock has been placed/found, bearing	°M from Mast/Plug/Pillar	Plug/Pillar	ļ .	oźz	+	
8. Action required			***************************************	8. Action required:	***************************************		1.1	seo /		
STANDPOINT:				STANDPOINT:			Ì	\ 00		
Mark	Direction	Horiz, Distance	Height Difference	Mark	Direction	Horiz. H	Height Difference	sk \		
			above standpr				standpt.	Ş40		
			above standpt.				above below standpt.			
			above standpt.					oez,		
			above standpt.				above below standpt,			
			acove standpt.				above standpt.			
			above standpt.				above standpt. No	ìzz		
			above standat.				above standpt.	2,10 / 2,00	190 180	170 160 150
Prepared by: A Kon		24/4/80	Checked:		Note	Noted on U.T.M. Card	Card		Checked	

ft 2733–2 D. West, Government Printer		STATION SMA 0892 TS 505
Beacon Diagram Not to Scale		
	Owner's Name:	Current Occupant:
	Address:	Address:
	. 0	Drone.
		ACCESS
	Access Report of//19was found suitable.unsuitable.	/unsuitable.
	Station not seen due to stand of trees on top	trees on top
	of same hill. Condition unknown (ould be used	ovid be used
	as a geodetic station.	
		w.
This section to be completed by officer constructing pillar,		¥
Original station mark found/not found.		
Description of mark:		
Original beacon found/not found.		
Description of beacon:	Date	Barord of Station
Height Top of Vanes to Top Mark	22	10,130,000,000,000,000,000,000,000,000,0
Height of mark selow rock/concm. below. G.L.		
Diameter of Vanesm., Height of Cairn		
Original Beacon has/has not been destroyed by me.		