EV OF N.S.W.	INO.: 57/	ords which do not apply SCALE 1:250 000 BEGA		AUTHORITY: FIELD BOOK:	, dimensions now being:	Station Disgram North North			Name Plate found/not found/placed.	<u>δ</u>	/ 04	from Mast/Plug/Pillar	M from Mast/Plug/Pillar	M from Mast/Plug/Pillar	100		Direction Distance Height Difference	720 No habuss mojec	tandpt	above sameda				des
CENTRAL MAPPING AUTHORITY GEODETIC SURVEY OF N.S.W	GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT	Description: Note: Cross out word or words which do not apply	1. Cleared by lanes bearing	2. Mast & Vanes have been painted white & black respectively.	3. The station/piliar was unpiled/not unpiled/constructed on19 dimensions now being:	Description of markshould be explicit, e.g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe	Height of markm. below rock/concrete; Mark ism. below G.L.	Height of Top Vanes to Top Mark/Pillar plate	Height of Cairn	Length of Mastm. (approximate if not unpiled)	4. A	5. Aset in conc/rock has been placed/found, bearing	6. Aset in conc/rock has been placed/found, bearing	7. Aset in conc/rock has been placed/found, bearing"M	8. Action required:	STANDPOINT:	Mark Direction Horiz. Height Difference Mark	ubove andpt.	above standpt.	above standpt.	AND	abowy standpt.	action standput to pelow stand	alcover below standpt. above below standpt. abover standpt.

2733-2 D. West, Government Printer	STATION S MA	SMA 0931. TS 571
Not to the control of	Owner's Name:	Gurrent Decupant:
	Phone:	Phone:
	ton and m	
	major clearing of lanes. Not suitable for geodefic station.	
This section to be completed by officer constructing piller.		
Original station mark found/not found. Description of mark:		
Description of beacon:	Date Record of Station	tion
reight of markn. below rock/concm. below G.L.		2
Diameter of Vanesm. Height of Caimm.		***************************************
Original beacon has/has not been destroyed by me.		