RECONNAISSANCE ond MAINTENANCE REPORT STATON TARANA G.S. Reconnational Transmitting Mest Transmitting Mest Transmitting Mest Transmitten Transmitting Mest Transmitten Transmit			
Note: Cross out word's words witch the not opply Note: Corr. Row Book Ph. Euro Book eenent 300: vision to serrounding Trigs. ing 200%	Department of Lands	RECONNAISSANCE and MAINTENANCE REPORT	TARANA
menni 360 vision to servending Trig. Mos Sheet: OBE ROW 1 1:00, 2000 Net: ing 320 %u - 200 %u, 200 %u - 200 %u, 200 %u, 200 %u - 200 %u	This Trig. Station has been:-	Note: Cross ou't word or words which do not apply	Roxsurgh
Hydelened to perminal 360° vision to summating Trip. University C. C.R. (202) Date: 3 y large bearing 252% 252% 242% 243% 247% End Bo y large bearing 252% 252% 248% 246% 247% End Bo y large bearing 252% 252% 248% 246% 247% 246% y large bearing 252% 252% 246% 246% 246% 246% y large bearing 252% 26% 26% 26% 26% 26% was unpled/act unpiled, alternapic now being: District to a short for a short for an explicit to a short for a short fo			OBERON 1 : 100,000
y lones bearing 2013a2013 M 243 M 244 M	1. Completely eleared to permit 360° visit	n to sunounding Trigs .	t i
# X Wanse how degre prive degrees a should be explicit, e.g. Shet prive degree defrementions now keing: Becen Drogram was unplied/stat.mglad, dimensions now keing: on of mork. <i>Cell</i> . <i>TRUG</i> . <i>PLOG</i> . <i>A. Serve.</i> should be explicit, e.g. Shet plug, blub, G.L. Prie Becen Drogram mork. <i>Cell</i> . <i>TRUG</i> . <i>PLOG</i> . <i>A. Serve.</i> should be explicit, e.g. Shet plug, blub, G.L. Prie Diameter of Vanes (vertical) <i>J. L. PLE</i> . n. Top Vanes to Top Mont. <i>J. J. L.</i> Diameter of Cairn. <i>2. E. m.</i> Diameter of Cairn. <i>2. E. m.</i> Top Vanes to Top Mont. <i>J. L. Max</i> Diameter of Cairn. <i>2. E. m.</i> Diameter of Cairn. <i>2. E. m.</i> Diameter of Cairn. <i>2. E. m.</i> Diameter of Vanes (vertical) Meret. Diameter of Cairn. <i>2. E. m.</i> Meret. Meret. Meret. Mest <i>J. J. Max</i> Meret. Meret. Meret. Meret. Meret. Meret. Meret. Meret.		1. 238.M. 243.M., 3/8.M. = 324.M., from Trig. Mast	C.M.A.
was urplied/aut.unpiled/ dimensions now being: an of mark. <i>Cu. 178, Q. 2019; A. cent.</i> should be explicit, e.g. Shel plug, Blars plug, Boli, G. Pipe mink. <i>Cu. 2063</i> m above eeck/concrete and the explicit, e.g. Shel plug, Blars plug, Boli, G. Pipe mink. <i>Cu. 2063</i> m above eeck/concrete and the explicit, e.g. Shel plug, Blars plug, Boli, G. Pipe Top Vanes to Top Monk 37702. m. Diameter of Vanes (vertical) 1.015 / m. Top Vanes to Top Monk 37702. m. Diameter of Vanes (vertical) 1.015 / m. Top Vanes to Top Monk 37702. m. Diameter of Caim. <i>2.5</i> m. Mast. <i>21.765.</i> /, an (approximate if not unpiled) Mast. <i>21.765.</i> /, m. (approximate if not unpiled) <i>M</i> from Trig. Mast <i>m. too</i> m. <i>m.</i> beoring <i>M</i> from Trig. Mast <i>m. too</i> m. <i>m.</i> beoring <i>M</i> <i>m. too</i> m. <i>m.</i> beoring <i>M</i> <i>m. too m. m.</i> beoring <i>M</i> <i>m. too m. too m.</i>		white & black respectively.	Beacon Diagram Not to Scale
an of mark. <i>Car. J. R. M. Concrete</i> alkold be explicit, e.g. Seel plug. Bols, G.I. Pre- mark. <i>C. O.663</i> m. alkold be explicit, e.g. Seel plug. Bols, G.I. Pre- mark. <i>C. O.663</i> m. alkold be explicit, e.g. Seel plug. Bols, G.L. Top Vanes to Top Mark 37:022. m. Diameter of Vanes (vertical) J. 015 f. m. Top Vanes to Top Mark 37:022. m. Diameter of Vanes (vertical) J. 015 f. m. Catim. <i>J.J.</i> m. Diameter of Catim. <i>2. S.</i> m. Mast. <i>33: J.165. J.</i> m. Diameter of Catim. <i>2. S.</i> m. Mast. <i>33: J.165. J.</i> m. Jaconing. <i>35:33</i> % from Trig. Mast set in conc/reck has been placed. <i>m.</i> bearing. <i>35:33</i> % from Trig. Mast set in conc/soil has been placed. <i>m.</i> bearing. <i></i> % from Trig. Mast set in conc/soil has been placed. <i>m.</i> bearing. <i></i> % from Trig. Mast set in conc/soil has been placed. <i>m.</i> bearing. <i></i> % from Trig. Mast <i></i> to <i>m.</i> bearing. <i>M</i> from Trig. Mast <i> is m. m.</i> bearing. <i>M</i> from <i> is m. m. m. m. m. m. m. m. m. m. m. m. m. </i>		sinsions now being:	(
mark O. 06.3 m above seek/concrete m more mark G.L. Top Vares to Top Mark 3.702m. Diameter of Vares (vertical) J. 0.15.m. Top Vares to Top Mark 3.702m. Diameter of Vares (vertical) J. 0.15.m. Cuim J.1. Diameter of Cuim 3.5 Mast 3.716.5m. Diameter of Vares (vertical) J. 0.15.m. Mast 3.716.5m. Diameter of Cuim Diffe set in conc/rock thas been placed m. bearing M from Trig. Mast Diffe set in conc/rock thas been placed m. bearing M from Trig. Mast Diffe set in conc/rock thas been placed m. bearing M from Trig. Mast Diffe set in conc/rock thas been placed m. bearing M from Trig. Mast Diffe set in conc/rock thas been placed m. bearing M from Trig. Mast Diffe set in conc/rock thas been placed m. bearing M from Trig. Mast Diffe set in conc/rock thas been placed m. bearing M from Trig. Mast Diffe set in conc/rock thas been placed m. bearing M from Trig. Mast Diffe set in conc/rock thas been placed M from Trig. Mast	Description of markCuTRUG. 24.00		1:0:2
Top Varies to Top Mark 3.702m. Diameter of Varies (vertical) J. P.P.F.m. Caim J./. m. Caim J./. m. Caim J./. m. Mast JJ.765m. (opproximate if not unpiled) Mast JJ.765m. Mont Trig. Mast PME In conc/soil has been placed m. bearing Miron Trig. Mast Miron Trig. Mast Set in conc/soil has been placed m. bearing Miron Trig. Mast Miron Trig. Mast Miron Trig. Mast Miron	Height of mark	rock /concrete	\rightarrow
Coin 11./. m. Diameter of Coin 3.5.7 m. Mast 3.7.165./.m. (approximate if not unpiled) Mast	Height of Top Vanes to Top Mark. 3.77)
Mast	Height of Cairn	r of Cairn 2.5	
OPEE_set in conc/eeck has been preced4: 7. m. bearing3530M from Trig. Mast 4: 7. m. bearing35.30M from Trig. Mast -set in conc/soil has been placedm. bearingm. bearing		roximate if not unpiled)	3:765
set in conc/soil has been placed	AG.J.P.P.E. set in conc/reck has	feored	
set in conc/soil has been placed	Aset in conc/soil has		
set in conc/rock has been placedm. bearingM from Trig. MastM from tom bearingM from Trig. MastM from trig. MastM from tom bearingM from trig. MastM from tom bearingM from trig. MastM from tom from trig. The from toM from tright from tr	Aset in conc/soil has	placed	
0n to			
0n to bearing M 0n to bearing M 0n to bearing M 0n to to bearing 0n to to to 0n to to to 0n to to to 0n to to to 15 m to to 15 m to to 15 to to to	Connection to.	m. bearing	
01	Connection to		
01	Connection to to to the to the top top to the top	m. bearing	-
	Connectionto	m. bearing	
2 IS	Diff. Hı.	have the second s	
is.	Diff. Ht.	meiowe meiowe	
		m. m. halowe	
IS			

.

Current Occupant			srst for approx. 5 km. 1904" Take this road. (0.0)/	н фАТЕ .	LLOW TRRCK TO LEFT.	۲۵. ۲۵. ۲۵.	राष्ट्र २० मध् <u>र</u>				
Owners NameS.MJ.T.H	Address P.h.one Xethelme. 25.7.	RE(ISED 2//11/ 1977 Access (Km) (OLP ACCESS OBSOLETE)	AT MEADOU FLAT take highway to Bathwet for approx. 5 km. with tood on left to Tarona. Sign "OBERON" Take this road. (0.0)/	2.7 STRAIGHT AHEAD GRAVEL ROAD ON RIGHT. 4.2.4 GATE ON RIGHT "BYALLA" GO THREUGH GATE . 4.2.4 O JUNED DAVED "	4.4. THROUGH TWO GATES SHOP ON RIGHT. FOLLOW TRRCK TO LEFT. / 4.4. RATULAN TWO GATES SHOP ON RIGHT. FOLLOW TRRCK TO LEFT. / 4.7. RATULAN FOLLOW FENCE LINK.	5.3. GATE: 5.9 GATE: 6.5 GATE: HEAD UP RIDGE 6.5 GATE: HEAD UP RIDGE					
Not to Scale	y de la contraction de la cont	and the second	 ຈາຍເ	h en an	and a second	and the second second	· · · · · · · · · · · · · · · · · · ·		Station Direction	Station	
Station Diagram	North	and the second	999919992			The second second	t.	d Directions:	Standpoint: June Charles June C	Station Direction	

. _____

_----

GEOD tion: by lanes bearing <u>25, and 5, 138, 5,</u> Vanes have been pained white & t in of pain van untimeted white & t in of mark. J.S.S. Junk, Matchould of mark. J.S.S.S. Junk, Matchould of mark. J.S.S.S. Junk, Matchould of Top Vanes to Top Matchould of Top Vanes to Top Matchould of Matchould of Matchould of Matchould of Matchould Matc	GEODETICS TATION RECONNAISSANCE and MAINTENANCE REPORT STATION: TaDackin CK. TaDackin CK. Luck Description: Description: State Report 1. Cleared by lanes bearing State (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c	A (1). hut 42 No. 15 5037 PL6(B-L I Les are are are are are are are are are are are
tion: by lanes bearing <u>55</u> to <u>15</u> , <u>158</u> to vares have been painted white & t is no of mark <u>355</u> m. <u>atrow</u> eek/out of mark <u>1555</u> m. <u>atrow</u> eek/out of Top Vanes to Top <u>Mark/Pillar</u> pl of Cairn		
Vanes have been painted white & t win/pillar was unpit Kathould tion of mark. S. S. Murkk, Kathould of mark. I. S. S. Murkk, Fillar pl of Cairn		
in of mark SAS. Rucht, Ketchould tion of mark SAS. Rucht, Ketchould of Top Vanes to Top Mark/Fillar pl of Cairn		
tion of mark. <u>3.5.5.</u> of mark. <u>1.3.5.5.</u> of Top Vanes to Top Mark /Fillar pl of Cairn	- · · · · · · · · · · · · · · · · · · ·	- 5
of mark. 1:252		
of Top Vanes to Top Mark/Fillar pl of Mast	ate	
of Cairn	Diameter of Cairn	
of Mast m. at a m. at the merc/rock p. 10. And the first merc/rock p. 10. And the merc/rock merc	proximate if not unpiled) has been p lace d/found, bearing. کریزین M from Manderug/Pillar has been placed/found, bearing. کریزین M from Manderug/Pillar has been placed/found, bearing. کریزین M from Mast/Plug/Pillar	
P.C. Line set in conc/rock P.E. set in conc/rock R.E. set in conc/rock required: <i>Er. intervie</i> (<i>III</i>), <i>F. F.N</i> required: <i>Er. intervie</i> (<i>III</i>), <i>F. F.N</i> Direction Distance N.C. D C. C. Direction Distance	has been p utere d/found, bearing. <u>자</u> °M from harmelo ug/Pillar has been p utere d/found, bearing. <u>자</u> °M from M <u>art/P</u> ug/Pillar has been placed/found, bearing. <u>자</u> °M from Mart/Plug/Pillar	
IPE set in conc/unsk Required: Ext intervision set in conc/rock Int: Direction Direction Distance Direction Distance	has been p lans d/found, bearing. <u></u> M from M aar/Di ug/Pillar has been placed/found, bearing. <u></u> M from Mast/Plug/Pillar has been placed/found, bearingM from Mast/Plug/Pillar	
Required: Ex. Interview Child, the Exh required: Ex. Interview Child, the Exh required: Ex. Interview Child, the Exh Direction Distance to Direction Distance to the to the to the to Direction Distance to the t	has been pieced/found, bearing.کیگی ^o M from htt st/Plug/Emilin has been placed/found, bearing ^o M from Mast/Plug/Pillar	
required: <i>Sc. intervision</i> Set in conc/rock INT: Reliance Link Rest Direction Distance I Direction Distance I Distance I Di Distance I Distance I Distance I	has been placed/found, bearing°M from Mast/Plug/Pillar	
Induired: for intervise (1,11), to fish INT: Richard Rights Direction Distance + Direction Distance + A O D C C	I	A
INT: PLLAR LATE Direction Distance I Direction Distance I Distance I Di Distance I Distance I Distance I	65 (10° to the right from Brick as ray) sport 3 days clouring westere couried 2	·m.
Direction Horiz. Distance Height Difference An P C C Balow sandpr An L C C Balow sandpr An L L S Balow sandpr	STANDPOINT: ELES TOL PLAC	8
Active standar Active standar	leight Difference Mark Direction Distance Height Difference	s 3,
Contraction in the second seco	altow standpt. LAM Lie CY of o co co below standpt.	
the standard	ethous atender build of 141 LT 35 below stander	REASS PLACE IN KACK
molen below	C. Pizz 292 16 4598 6212 below standbur Par	([mub])
- C	1.671 Delow standar PILLAR PLATE 322 35 23 12 012 7. 46	
below standpt	Palow standpt.	- z ₁ ,
atove standpt. below	below standpt.	
<u>م</u> م	abnve standpt.	190 180 170 160 150
Prepared by: Ve Vark, 7.3-75 Checked: 2-22		Checked

o e em le 5 marches e en else else

St 2733–2 D. Wast, Government Printer	STATION TALENA CI PILAR TS 6037
Beacon Diagram Not to Scale	

	UA TALANA.
Mars Could D. Keswi	A DOURS MARKED AND A DOURS AND A
	Access Report of 3.1.4.197, was found suit de/unsuitable.
	PO. TAPANA HEAD EART
	and Okeral O'Ewsell, Annuer,
	OLO WASH JUNE RANNING STRATISTIC THERE STATE WE ALSO THE REPORT OF A
	O. 15 WARDEN BRIDERE (Sar ITARY REEZ)
	10.10
	-
	Les thes hear on hat can be as the action of actions the second state of and the second state of actions of the second state o
10 1 10 1 10 1 10 10 10 10 10 10 10 10 1	0.15 Tugu Left Sign Blanch Tugaden Igal Cherk
This section to be completed by officer constructing pillar.	
Original station mark found/not found.	Téch
Description of mark:	to Sa Ilbart Burth 11 NA Thesi Armentess of time verts on right Configure stratist admini cannon reasoned and the character
	· -9
A. 01 An 144	12.cc through yellow punked iren gate, veer left then right lefowing faint track justif force line on right 13.74 St. Bandis, Ganarian fail down, find annum 18.64,2000 for an and an and an a
Description of beacon:	1 2 0 00 00 00 00 00 00 00 00 00 00 00 00
Height Top of Vanes to Top Mark	13. 2 TARAUP
Height of mark@.BR.3.m. hereve week/ence.G.BAF.m. acuse G.L. Dismonses for the Article Art Article Art Article Art Article Art	Bernaliuely - keep traveling with ferce line on right to fence corner al 13.55. Leave vehicle here and wells for represe. 250m. Ib Hig.
Delineral OF valles, American, Manual Ma	Date Record al Stoken

TS6037 | Print Date: 31/05/2022 17:13 | No Of Pages: 4 | Property of DFSI – Spatial Services

GS