	GEODETIC	STATION REC	ETIC STATION RECONNAISSANCE and MAINTENANCE REPORT	d MAINTENA	NCE REPORT	STATION:	******	ANDERSON	_	No.: 624
Description:		Note: C	Note: Cross out word or words which do not apply	ords which do	not apply	MAP SHEET SCALE 1:250 000	ET 250 000	CANBERRA		
Cleared by lanes bearing from Trig. Mast			***************************************	from Triẹ	J. Mast	INSPECTED BY:		G.C.HANNA	DATE:	25/4/79
Mast & Vanes have been painted white & black respectively,	ed white & black r	espectively.		/	\	AUTHORITY:	10000	C.M.A.	FIELD BOOK:	oK:
The station/pillar was unpiled/not unpiled/constructed on19	not unpiled/const	ructed on	19	, dimensions r	ow being:	330	340	350 360	10 / 2¢	/ 30/
Description of markmshould be explicit, e.g., S/ Height of markm.m. ^{abous} rock/concrete; M:	bove rock/concretelow rock/concretelow	cplicit, e.g., S/Ste; Mark	be explicit, e.g., S/Steel Pillar Plate, Bfeel plug, Brass plug, Bolt, G.L. Pipe ncrete; Mark is	Breel plug-Brass p	Plate Steel plug, Brass plug, Bolt, G.I. Pipe	928	Station Diagram	North	Not	Not to Scale
Height of Cairn	Dia	Diameter of Caira		me Plate foun	Name Plate found/not found/placed.	018 /				
Length of Mastm.		(approximate of not unpiled)	(pal)			90°E				
Aset in peace/rock has been placed/found, bearing"M from Mast/Plug/Pillar	Leonc/rock Has be	en placed/found	d, bearing	M from Mast	Plug/Pillar	/0				
AA. set in conc/rock has been placed/found, bearingM from Mast/Plug/Pillar	corre/rock has be	en placed/found	d, bearing	M from Mast,	'Plug/Pillar	şź / c				
		en placed/founc	nas been placed/found, bearing"M from Mast/Plug/Pillar	M from Mast	'Plug/Pillar	ośz o		-		
7. A	conc/rock has be	en placed/founc	nas been placed/found, bearing"M from Mast/Plug/Pillar	M from Mast.	Plug/Pillar	04Z 09Z		+		
STANDPOINT:			STANDPOINT:			: \ 09				
Mark Direction	Horiz, Distance Height I	Height Difference	Mark	Direction	Horiz. Height Difference	1				
	e A	above standpt.			olad olad	above standpt. N				
	a 1	above standpt.			ole about	above below standpt.				
	8.1	above standpt.			above below ^s	above tandpt, N				
		above standpt.			abov belo	above standpt.				
	a, D	above below standpt.			abov Delo	above standpt,				
		above standpt.			abov	above standpt, No below				
		above standpt.			above below	above standpt. 210	200	081 061	170 160	150
Preciared for Off	20/1/20	Charked.		10/0	Motor of T. M. Cond			Chapter		

Not to Seale Not to Seale Address: A	St 2733-2 D. West, Government Printer	STATION	ANDERSON 624
Access R Acc	Beacon Diagram Not to Scale	N. T. C.	
# Access P A		Owner's vame:	Current Occupant:
Access R Acc		Address:	Address:
Access R Access R Access R Below G.L. Brit of Gaim		Риль	D
Access R Not for Boillar. Brillar. Access B Not for Boile Brillar. Above G.L. Brillar. Brillar. Brillar. Brillar. Brillar.			TIOUE.
g pillar. G pillar. Date Date Lebove G.L. sht of Caim		Access Report of 25/. 2./19.79was found suitable/unsuitable.	
g pillar. Babove G.L. Bat of Caim			
g pillar. Babove G.L. Bht of Gaim		Not tound.	
gpillar. Date			
gpillar. Date			
g pillar. Brillar.		1	
g pillar. Babove G.L. Batto Caim			
g pillar. Date m. above G.L. below G.L. aht of Caim			
g pillar. Date n. above G.L. below G.L. aht of Caimm.			
g pillar. Date above G.L. bht of Caim			
g pillar. Date above G.L. bilow G.L. aht of Caim			
Daten. above G.L. below abt of Caim	s section to be completed by officer constructing pillar.		
above G.L. below G.L.	iginal station mark found/not found.		
Date above G.L. below fit of Caim			
Date above G.L. aht of Caim	iginal beacon found/not found.		
above G.L. helow and control of the	scription of beacon:		
above G.L. below aht of Caimm.	ght Top of Vanes to Top Markm.		d of Station
ght of Caim	ght of markm. below rock/concm. below G.L.		
	meter of Vanesm. Height of Cairnm.		
	ginal Beacon has/has not been destroyed by me.		