

CENTRAL MAPPING AUTHORITY

GEODETIC SURVEY OF N.S.W.
 GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT

STATION: **BELLALEPPA** No.: **6704**
 MAP SHEET SCALE 1:250 000
 INSPECTED BY: **J. FANNING** DATE: **15/2 Aug 80**
 AUTHORITY: **C.M.A. NSW 219** FIELD BOOK: **1837**

- Description: *Note: Cross out word or words which do not apply*
- Cleared by lance-bearing *(crossed out)* from Trig. Mast
 - Mast & Vanes have been painted white & black respectively.
 - The station/pillar was unpiled/not unpiled/constructed on *19* dimensions now being:
 - Description of mark *should be explicit, e.g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe*
 - Height of mark *above/below* rock/concrete; Mark is *above/below* G.L.
 - Height of Top Vanes to Top Mark/Pillar plate *m.* Diameter of Vanes (vertical) *m.*
 - Height of Cairn *m.* Diameter of Cairn *m.* Name Plate found/not found/placed.
 - Length of Mast *m.* (approximate if not unpiled)
 - A *set in conc/rock has been placed/found, bearing *°M* from Mast/Plug/Pillar*
 - A *set in conc/rock has been placed/found, bearing *°M* from Mast/Plug/Pillar*
 - A *set in conc/rock has been placed/found, bearing *°M* from Mast/Plug/Pillar*
 - A *set in conc/rock has been placed/found, bearing *°M* from Mast/Plug/Pillar*
 - Action required: *Erect conc pillar plate & witness marks 1-2 days clearing*

STANDPOINT:		STANDPOINT:		STANDPOINT:			
Mark	Direction G.R.D.	Horiz. Distance	Height Difference	Mark	Direction G.R.D.	Horiz. Distance	Height Difference
BERRIBERRY	30°	11.5	Mirror above standpt. Flashes below	BERRIBERRY	10	14	Flashes above standpt. below
East Bluff	34°	34	Hill above standpt. below	WONGALEE	326	19.5	Hill above standpt. below
Howard	85°	22.6	M.V. above standpt. below				
Walt	129	22.9	Hill above standpt. below	Borombil	262	9.2	Hill above standpt. below
Torill	278	19.5	M.V. above standpt. below	Cranborne	66	2.0	Flashes above standpt. below
Boydmanna	310	35	M.V. above standpt. below	Summer			Flashes above standpt. below
CUMS	357	21.1	Hill above standpt. below				

Prepared by: **J. FANNING** Checked: *4/7/80* Noted on U.T.M. Card

GS 24

<p>STATION <u>BELLALLEPPA 6704</u></p>	<p>Owner's Name: <u>Michael Elliot</u> Address: <u>Cattle Creek</u> Phone: <u>Casilis 23 K</u></p> <p>Current Occupant: Address: Phone:</p> <p style="text-align: center;"><u>ACCESS</u></p> <p>Access Report of <u>V.O.S. 119880</u> was found suitable/unsuitable.</p> <p><u>0-0 P.O. Casilis travel east towards Merrina</u> <u>8-0 Cross Barrow hill Creek</u> <u>8-23 Turn left onto dirt road</u> <u>8-27 8-26 9-24 } Grid</u> <u>10-32 11-60 13-47 } Grid</u> <u>14-94 Pass house RHS</u> <u>15-55 Grid. Turn right off track and go up hill to South</u> <u>16-3</u></p> <p><u>Owner House</u></p> <p><u>0-0 P.O. Casilis travel towards Pomal 1 block turn right</u> <u>8-1 Turn right Signpost Condo Bulba</u> <u>8-5 Take left fork</u> <u>10-5 house on RHS</u></p>												
<p>Beacon Diagram</p> <p style="text-align: right;">Not to Scale</p>	<p>This section to be completed by officer constructing pillar.</p> <p>Original station mark found/not found.</p> <p>Description of mark:</p> <p>Original beacon found/not found.</p> <p>Description of beacon:</p> <p>Height Top of Vanes to Top Mark.....m. above G.L. below</p> <p>Height of mark.....m. rock/conc.....m. above G.L. below</p> <p>Diameter of Vanesm. Height of Cairnm.</p> <p>Original Beacon has/has not been destroyed by me.</p>												
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Date</th> <th>Record of Station</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1st Sept 80</td> <td>Verbal permission given by owner to erect pillar & do any clearing necessary.....</td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> </tbody> </table>	Date	Record of Station	1st Sept 80	Verbal permission given by owner to erect pillar & do any clearing necessary.....								
Date	Record of Station												
1st Sept 80	Verbal permission given by owner to erect pillar & do any clearing necessary.....												

CENTRAL MAPPING AUTHORITY GEODETTIC SURVEY OF NS/IM

GEODETTIC STATION RECONNAISSANCE and MAINTENANCE REPORT

STATION: BELLELUPA (P)	No: 6704
MAP SHEET SCALE 1:250 000	SINGLETON
INSPECTED BY: W. McEILIVRAY	DATE: 5-5-81
AUTHORITY: C.M.A.	FIELD BOOK: 1818

Station Diagram

Description:	PILLAR		STANDPOINT: CORNER		MATT	
	Mark	Direction	Horiz. Distance	Height Difference	Direction	Horiz. Distance
1. Cleared by lanes bearing 153.30° and 262.28° from Trig. Mast						
2. Mast & Vanes have been painted white & black respectively.						
3. The station/pillar was unplaced /constructed on 19.8 m. dimensions now being:						
Description of mark: 100 m. S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe						
Height of mark: 3.85 m. above G.L.						
Height of Top Vanes to Top-Mast/Pillar plate 1.43 m. Diameter of Vanes (vertical) 0.75 m.						
Height of Cairn: m. Diameter of Cairn: m. Name Plate found /not found/placed.						
Length of Mast: 1.51 m. (approximate if not unpled)						
4. A. CORNER MATT set in conc/rock has been placed/removed, bearing 87.3° M from Mast/Plug/Pillar						
5. A. CORNER MATT set in conc/rock has been placed/removed, bearing 37.3° M from Mast/Plug/Pillar						
6. A. set in conc/rock has been placed/removed, bearing M from Mast/Plug/Pillar						
7. A. set in conc/rock has been placed/removed, bearing M from Mast/Plug/Pillar						
8. Action required:						

Mark	Direction	Horiz. Distance	Height Difference	STANDPOINT: CORNER		MATT	
				Direction	Horiz. Distance	Height Difference	Direction
BORAMBUI PILLAR	359	59	60	359	59	60	
G.I. P. PE	92	07	55	10	35	10	3.386
CORNER MATT	190	34	26	51	07	55	5.107
MATT PILLAR	228	07	55	228	07	55	
HOWARD PILLAR	194	03	06	194	07	50	

Prepared by: Checked: Noted on U.T.M. Card

GS24

<p>STATION BELLALUPA PILLAR 6704</p>	<p>Owner's Name: M.S.H.A.K. ELALOT Address: CASSILIS CRACK Phone: CASSILIS 23.K</p> <p>Current Occupant: Address: Phone:</p> <p>ACCESS Access Report of 5.5/19.8 was found suitable/unsuitable.</p> <p>0-0 POST CASSILIS TRAVEL TOWARDS MERRAWA 8-0 CROSS BORAMBIL CREEK. 8-23 TURN LEFT ONTO DIRT ROAD 8-27 GRID 8-86, 9-24, 10-32, 11-60, 13-67. 14-94 PASS HOUSES ✓ SURDS, 15-55 GRID. TURN HARD RIGHT FOLLOW FAINIT UP HILL TO GS. 16-30 GS.</p>
<p>Beacon Diagram</p> <p>Not to Scale</p>	<p>This section to be completed by officer constructing pillar.</p> <p>Original station mark found/not found.</p> <p>Description of mark:</p> <p>Original beacon found/not found.</p> <p>Description of beacon:</p> <p>Height Top of Vanes to Top Markm. above below G.L. Height of markm. above rock/cone below Diameter of Vanesm. Height of Cairnm. Original Beacon has/has not been destroyed by me.</p>
<p>Date</p>	
<p>Record of Station</p>	