

TS 6713

GEODETIC SURVEY OF N.S.W.

CENTRAL MAPPING AUTHORITY

GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT

STATION: **QUIPINDI** No.: **2830**
 MAP SHEET SCALE 1:250 000 **TAMWORTH**
 INSPECTED BY: **D. KINLYSIDE** DATE: **23rd Oct 20**
 AUTHORITY: **C.M.A. NSW 229** FIELD BOOK: **1905**

- Description: *Note: Cross out word or words which do not apply*
- Cleared by lanes bearing **Not Clear** from Trig. Mast
 - Mast & Vanes have been painted white & black respectively.
 - The station ~~is not~~ **is** unpiled/constructed on **3.1.1.1.1** dimensions now being: Description of mark should be explicit, e.g. S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe
 Height of mark^{above} rock/concrete; Mark is^{above} m. ^{below} G.L.
 Height of Top Vanes to Top Mark/Pillar plate m. Diameter of Vanes (vertical)^{0.95} m.
 Height of Cairn^{1.7} m. Diameter of Cairn m. Name Plate ~~found~~/not found/**replaced**.
 Length of Mast^{3.7} m. (approximate if not unplied)
 - Ab witness marks found** set in conc/rock has been placed/found, bearing ° M from Mast/Plug/Pillar
 - A** set in conc/rock has been placed/found, bearing ° M from Mast/Plug/Pillar
 - A** set in conc/rock has been placed/found, bearing ° M from Mast/Plug/Pillar
 - A** set in conc/rock has been placed/found, bearing ° M from Mast/Plug/Pillar
 - Action required: **Construct & clear track to Trig. Feet conc pillar + 2 witness marks + 2 day clearing**

STANDPOINT:			
Previously Observed	Grid Direction	Horiz. Distance	Height Difference
Warrak View	210 14	16.6	above standpt.
Fair Mile	251 34	7.5	below standpt.
MetHam	287 01	10.6	above standpt.
Barpard	62 24	11.9	below standpt.
			above standpt.
			below standpt.
			above standpt.
			below standpt.

Prepared by: **J. Fanning** Checked: **R. Holton** *Notes on U.T.M. Card*

GS 24

STATION QUIRINDI G.S. TS 6713

Owner's Name: Alan Pine
 Address: Poissonnet
 Phone: Quirindi 388

Current Occupant:
 Address:
 Phone:


ACCESS

Access Report of 23/10/1988 was found suitable/unsuitable.

- 0.0 Marshall McMahon Hotel Wallebadah Travel North.
- 8.35 Turn left towards Quirindi.
- 8.34 Turn left Sp "Carinya 6"
- 8.72 through gate to owners house
- 9.48 Turn left. Stay on main road
- 9.82 Causeway
- 12.61 Double iron gate
- 12.65 Take right fork
- 12.94 thru iron gate & turn right
- 14.36 Iron gate
- 16.11 wire gate yards on right
- 16.37 wire gate
- 16.54 Dam on right
- 16.65 Turn right through wire gate follow track marked with orange tape on trees (until first bushfire)
- 18.27 At blazed tree Trig is 2 min walk to right. May be driven to by continuing straight ahead and approaching hill from west if track is cleared

Not to Scale

Beacon Diagram



This section to be completed by officer constructing pillar.

Original station mark found/not found.

Description of mark:

Original beacon found/not found.

Description of beacon:

Height Top of Vanes to Top Markm.

Height of markm. above G.L. below

Diameter of Vanesm. Height of Cairnm.

Original Beacon has/has not been destroyed by me.

Date

Record of Station

23rd Oct 88 Permission to Pillar & Clear received from Owner

STATION: QUIRINDI (P) No. TS 3830
GS6713

MAP SHEET SCALE 1:250,000

INSPECTED BY: S L MASTERS DATE: 1/3/89

AUTHORITY: RTA FIELD BOOK: —

Not to Scale
 PROJECT DEVELOPMENT SECTION (218-6780)
 SURVEY GROUP

ACCESS + ONLY

Checked 2/11/90

GEODETTIC STATION RECONNAISSANCE and MAINTENANCE REPORT

Description:

1. Cleared by James bearing.....
 Note: Cross out word or words which do not apply

2. Mast & Vanes have been painted white & black respectively.
 from Trig. Mast

3. The station/pillar was unpiled/not unpiled/constructed on..... 19....., dimensions now being:
 Description of mark.....should be explicit, e.g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe
 Height of mark.....m. above rock/concrete; Mark is.....m. above below G.L.
 Height of Top Vanes to Top Mark/Pillar plate.....m. Diameter of Vanes (vertical).....m.
 Height of Cairn.....m. Diameter of Cairn.....m. Name Plate found/not found/placed.
 Length of Mast.....m. (approximate if not unpiled)

4. A.....set in conc/rock has been placed/found, bearing.....° M from Mast/Plug/Pillar

5. A.....set in conc/rock has been placed/found, bearing.....° M from Mast/Plug/Pillar

6. A.....set in conc/rock has been placed/found, bearing.....° M from Mast/Plug/Pillar

7. A.....set in conc/rock has been placed/found, bearing.....° M from Mast/Plug/Pillar

8. Action required:.....

STANDPOINT:

Mark	Direction	Horiz. Distance	Height Difference	Mark	Direction	Horiz. Distance	Height Difference
			above standpt.				above standpt.
			below standpt.				below standpt.
			above standpt.				above standpt.
			below standpt.				below standpt.
			above standpt.				above standpt.
			below standpt.				below standpt.
			above standpt.				above standpt.
			below standpt.				below standpt.
			above standpt.				above standpt.
			below standpt.				below standpt.

Prepared by:..... Checked:..... 2/11/90 Noted on U.T.M. Card

S 2733-1

