

GEODETTIC SURVEY OF N.S.W

CENTRAL MAPPING AUTHORITY

GEODETTIC STATION RECONNAISSANCE and MAINTENANCE REPORT

STATION: **SYLVIA VALE** No.: **7143**  
 MAP SHEET SCALE 1:250 000 **GOULBORN**  
 INSPECTED BY: **L. HITCHINS** DATE: **22-5-84**  
 AUTHORITY: **C.M.A** FIELD BOOK: **1821**

- Description:
- Cleared by lanes bearing **360°**. Note: Cross out word or words which do not apply from Trig. Mast
  - Mast & Vanes have been painted white & black respectively.
  - The station/pillar was ~~unplaced/not unplaced~~/constructed on **1st MAY 1984**, dimensions now being: Description of mark **S/S PILLAR PL** should be explicit, e.g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe Height of mark **1.271** above below ~~rock~~/concrete; Mark is **1.751** above below G.L. Height of Top Vanes to Top ~~Mark~~/Pillar plate **1.435** m. Diameter of Vanes (vertical) **0.750** m. Height of Cairn ~~.....~~ m. Diameter of Cairn ~~.....~~ m. Name Plate ~~found/not found~~/placed. Length of Mast ~~.....~~ m. (approximate if not unplaced)
  - A **S/S TRIC PILLAR** **1** set in conc/~~rock~~ has been ~~placed~~/found, bearing **29.7** °M from Mast/Plug/Pillar
  - A **COPPER NAIL** **2** set in conc/~~rock~~ has been ~~placed~~/found, bearing **50** °M from Mast/Plug/Pillar
  - A **C.I. PIPE** **3** set in conc/~~rock~~ has been ~~placed~~/found, bearing **3.1** °M from Mast/Plug/Pillar
  - A ~~.....~~ set in conc/~~rock~~ has been ~~placed~~/found, bearing ~~.....~~ °M from Mast/Plug/Pillar

8. Action required: ~~.....~~

STANDPOINT: <b>S/S PILLAR PLATE</b>		STANDPOINT: <b>S/S TRIC PILLAR</b>	
Mark	Direction	Mark	Direction
WELLS CS (M)	0 00 00	WELLS CS (M)	0 00 00
S/S TRIC PILLAR	30 12 50	C.I. PIPE	35 08 30
C.I. PIPE	31 30 30	COPPER NAIL	127 22 25
COPPER NAIL	50 51 45	MARAWA CS (M)	195 23 55
MARAWA CS (M)	195 23 55	S/S PILLAR PLATE	210 13 50

Prepared by: **[Signature]** Checked: **15-4-84** Noted on U.T.M. Card **40 30 1184**  
 Checked **100 30 1184**

