150

160

170

180

200

210

above standpt. standp1.

above

Noted on U.T.M. Card

16/2/2

Frepared by: 6 201 5/3/9

St 2735-1

above standpt. above standpt. Checked:

Checked 190

FIELD BOOK: C 609 No.: 7331 1:100 000 DATE: 23/2/9/ Not to Scale R13-ととん 23 EAST GEKARA 2.46 FORD 360 STATION: MILE POST 350 N.S.W /QLD BOKDER ONFEE Station Diagram. 350 MAP SHEET SCALE 1:250 000 INSPECTED BY: AUTHORITY: 330 560 below standpt,
above standpt,
above standpt,
below standpt,
telow standpt,
telow standpt,
below; standpt, Height Difference Rober Id Name Plate found/not found/placed. Nail pld in projected contre of mile part.

Description of mark......should be explicit, e.g., S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe Action required: Diameter of Vanes (vertical).....m. GEODETIC STATION RECONNAISSANCE and MAINTENANCE REPORT As recovery the state of the st RM2 Set in conclude has been placed/found, bearing.3/k.... M from Mast/Plug/Fillar A.....23 Mills Pos 7 set in concitock has been placed/found, bearing 34:8 M from Maxt Plug Pillar Note: Cross out word or words which do not apply Horiz. Distance Cleared by lanes bearing. Fax. G.P.S. from Trig. Mast Direction GEODETIC SURVEY OF N.S.W. Mark is...... m. above G.L. STANDPOINT Diameter of Cairn.....m. Mark Length of Mast ......m. (approximate if not unpiled) 2 0-26 shove standpt.
2 0-26 shove standpt.
2 below standpt.
2 below standpt.
8 shove standpt.
8 shove standpt. Mast & Vanes have been painted white & black respectively. Height Difference Height of mark.....m. m. below rock/concrete; 55 50 4.972 0.201 Height of Cairn.....m, Horiz. Distance 93 42 10 5.043 00 00 0 LAND INFORMATION CENTRE Direction 8 7 OLD 23 HILE POST GINAL INGUM Description: STANDPOINT Mark 7. N က် ø. 4 ໝ່

Beacon Diagram No; to Scale	Owner's Name: BILL RIDGE  Current Occupant: Address: Addr
	Phone: UNF CHAINER 36  ACCESS Access Report of 22 1/1991 was found suitable/unsuitable.  O: 40 ENNCONIA HOTEL HEAD NORTH
	20.73 TURN RICHT INTO LAWE JUST AFTER CKID MAIL BOX "BIRRIMBA" 25.33 IRON GATES 28.05 TAKE RICHT FORK 31.63 ILON CATE 38.52 I RAW CATE 40.63 IRON CATE 41.61 TURN LEFT BEFORE MAIN HOUSE COTTAGE ON R.H.S. 43.55 CATE FOLLOW TRACK STRAIGHT AHEAD
This section to be completed by officer constructing pillar.  Original station mark found/not found.  Description of mark:	GATE GATE GATE BOKE DR TURN LU TRON GA
Original beacon found/not found. Description of beacon:	34 23 MILE DOS
	Date Record of Station