

GEODETTIC SURVEY OF M.S.W.

CENTRAL MAPPING AUTHORITY

GEODETTIC STATION RECONNAISSANCE and MAINTENANCE REPORT

STATION: **BERTHONG G.S.** No.: **889**

MAPSHEET SCALE 1:250 000 **COOYAMUNDRA**

INSPECTED BY: **L. HITCHINGS** DATE: **22.1.20**

AUTHORITY: **C.M.A.** FIELD BOOK: **DISDS**

Station Diagram

North

**VANES HAVE "ROCK LOOK"**

**STAMPED ON THEM**

+

Not to Scale

Description:

- Cleared by lanes bearing **360°M**. Note: Cross out word or words which do not apply from Trig. Mast
- Mast & Vanes have been painted white & black respectively.
- The station/pillar was ~~unplaced/erected~~ constructed on **2.2.1.20.18**, dimensions now being: Description of mark **BRASS PILLAR** should be explicit, e.g. S/Steel Pillar Plate, Steel plug, Brass plug, Bolt, G.I. Pipe Height of mark **0.275** m. above ~~rock~~ concrete; Mark is **AT** above G.L.
- Height of Top Vanes to Top Mark/Pillar plate **2.990** m. Diameter of Vanes (vertical) **2.925** m.
- Height of Cairn **1.260** m. Diameter of Cairn **1.9** m. Name Plate found/not found/placed.
- Length of Mast **3.075** m. (approximate if not unplied)
- A. set in conc/rock has been placed/found, bearing.....° M from Mast/Plug/Pillar
- A. set in conc/rock has been placed/found, bearing.....° M from Mast/Plug/Pillar
- A. set in conc/rock has been placed/found, bearing.....° M from Mast/Plug/Pillar
- A. set in conc/rock has been placed/found, bearing.....° M from Mast/Plug/Pillar
- Action required:.....

STANDPOINT:					
Mark	Direction	Horiz. Distance	Height Difference	Mark	Height Difference
			above standpt.		above standpt.
			below standpt.		below standpt.
			above standpt.		above standpt.
			below standpt.		below standpt.
			above standpt.		above standpt.
			below standpt.		below standpt.
			above standpt.		above standpt.
			below standpt.		below standpt.
			above standpt.		above standpt.
			below standpt.		below standpt.

Prepared by: **L. Hitchings** Checked: **L. Hitchings** Noted on U.T.M. Card

Checked

